



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECint[®]2006 = 25.3

SPECint_base2006 = 21.7

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E3110
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (4x2 GB) FB-DIMM PC2-6400E ECC CL6
 Disk Subsystem: 1x73 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1
 Kernel 2.6.16.46-0.12-smp for x86_64
 Compiler: Intel C++ Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Binutils 2.17.50.0.15
 SmartHeap library V8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECint2006 = 25.3

SPECint_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	495	19.7	501	19.5	<u>497</u>	<u>19.7</u>	<u>397</u>	<u>24.6</u>	395	24.7	398	24.6
401.bzip2	<u>581</u>	<u>16.6</u>	581	16.6	581	16.6	537	18.0	536	18.0	<u>537</u>	<u>18.0</u>
403.gcc	378	21.3	<u>379</u>	<u>21.3</u>	380	21.2	352	22.9	352	22.9	<u>352</u>	<u>22.9</u>
429.mcf	<u>332</u>	<u>27.4</u>	332	27.5	333	27.4	<u>334</u>	<u>27.3</u>	333	27.4	334	27.3
445.gobmk	540	19.4	540	19.4	<u>540</u>	<u>19.4</u>	<u>476</u>	<u>22.0</u>	476	22.0	476	22.0
456.hmmmer	<u>594</u>	<u>15.7</u>	594	15.7	593	15.7	341	27.3	<u>341</u>	<u>27.4</u>	340	27.4
458.sjeng	658	18.4	661	18.3	<u>659</u>	<u>18.4</u>	589	20.6	<u>590</u>	<u>20.5</u>	590	20.5
462.libquantum	495	41.8	496	41.7	<u>496</u>	<u>41.7</u>	325	63.8	<u>325</u>	<u>63.8</u>	324	63.9
464.h264ref	711	31.1	<u>698</u>	<u>31.7</u>	698	31.7	<u>666</u>	<u>33.2</u>	671	33.0	665	33.3
471.omnetpp	<u>335</u>	<u>18.6</u>	336	18.6	335	18.6	306	20.4	<u>307</u>	<u>20.4</u>	310	20.2
473.astar	455	15.4	451	15.6	<u>452</u>	<u>15.5</u>	408	17.2	407	17.2	<u>408</u>	<u>17.2</u>
483.xalancbmk	253	27.3	<u>253</u>	<u>27.3</u>	252	27.4	253	27.3	<u>253</u>	<u>27.3</u>	252	27.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to null
```

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmmer, for peak, are compiled in 64-bit mode

The Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz), the Bull NovaScale T830 E1(Intel Xeon E3110, 3.00 GHz) and the Bull NovaScale R410 E1(Intel Xeon E3110, 3.00 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz) model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECint2006 = 25.3

SPECint_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control
C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc
401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include
456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include
C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECint2006 = 25.3

SPECint_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalanbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmr: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

483.xalanbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T810 E1
(Intel Xeon E3110, 3.00 GHz)

SPECint2006 = 25.3

SPECint_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 20:00:55 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.