



# SPEC<sup>®</sup> CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECint<sup>®</sup>2006 = 40.7

NovaScale T860 F2 (Intel Xeon X5667, 3.06 GHz)

SPECint\_base2006 = 37.8

CPU2006 license: 20


Test date: Mar-2010

Test sponsor: Bull SAS

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009



### Hardware

CPU Name: Intel Xeon X5667  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.46 GHz  
 CPU MHz: 3067  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 12 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 x 4 GB DDR3-1333 DR RDIMM)  
 Disk Subsystem: 2 x 300 GB 10000 RPM SAS  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64), Kernel 2.6.27.19-5-smp  
 Compiler: Intel C++ Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l\_cproc\_p\_11.1.064  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECint2006 = 40.7

NovaScale T860 F2 (Intel Xeon X5667, 3.06 GHz)

SPECint\_base2006 = 37.8

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Dell Inc.

Test date: Mar-2010  
Hardware Availability: Mar-2010  
Software Availability: Dec-2009

## Results Table

| Benchmark      | Base              |                    |                    |                    |                   |                    | Peak              |                    |                   |                    |                    |                    |
|----------------|-------------------|--------------------|--------------------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------------------|--------------------|--------------------|
|                | Seconds           | Ratio              | Seconds            | Ratio              | Seconds           | Ratio              | Seconds           | Ratio              | Seconds           | Ratio              | Seconds            | Ratio              |
| 400.perlbench  | 363               | 26.9               | 364                | 26.8               | <b><u>364</u></b> | <b><u>26.9</u></b> | 313               | 31.2               | 313               | 31.2               | <b><u>313</u></b>  | <b><u>31.2</u></b> |
| 401.bzip2      | 474               | 20.4               | <b><u>474</u></b>  | <b><u>20.4</u></b> | 474               | 20.4               | 474               | 20.4               | 473               | 20.4               | <b><u>474</u></b>  | <b><u>20.4</u></b> |
| 403.gcc        | 316               | 25.5               | 317                | 25.4               | <b><u>316</u></b> | <b><u>25.5</u></b> | 283               | 28.5               | 282               | 28.5               | <b><u>282</u></b>  | <b><u>28.5</u></b> |
| 429.mcf        | 205               | 44.5               | 206                | 44.4               | <b><u>205</u></b> | <b><u>44.5</u></b> | 179               | 51.0               | <b><u>180</u></b> | <b><u>50.8</u></b> | 184                | 49.7               |
| 445.gobmk      | 418               | 25.1               | <b><u>417</u></b>  | <b><u>25.2</u></b> | 416               | 25.2               | 383               | 27.4               | 383               | 27.4               | <b><u>383</u></b>  | <b><u>27.4</u></b> |
| 456.hmmr       | <b><u>191</u></b> | <b><u>48.8</u></b> | 191                | 48.8               | 191               | 49.0               | 185               | 50.3               | <b><u>185</u></b> | <b><u>50.3</u></b> | 185                | 50.3               |
| 458.sjeng      | 452               | 26.8               | <b><u>452</u></b>  | <b><u>26.8</u></b> | 453               | 26.7               | 436               | 27.8               | <b><u>436</u></b> | <b><u>27.8</u></b> | 436                | 27.7               |
| 462.libquantum | 36.0              | 575                | <b><u>35.4</u></b> | <b><u>585</u></b>  | 35.2              | 588                | 35.0              | 592                | 35.8              | 578                | <b><u>35.0</u></b> | <b><u>592</u></b>  |
| 464.h264ref    | 576               | 38.4               | <b><u>576</u></b>  | <b><u>38.4</u></b> | 575               | 38.5               | 526               | 42.1               | 524               | 42.2               | <b><u>524</u></b>  | <b><u>42.2</u></b> |
| 471.omnetpp    | 277               | 22.5               | <b><u>277</u></b>  | <b><u>22.6</u></b> | 276               | 22.6               | 220               | 28.5               | <b><u>220</u></b> | <b><u>28.5</u></b> | 220                | 28.4               |
| 473.astar      | 333               | 21.1               | <b><u>332</u></b>  | <b><u>21.1</u></b> | 331               | 21.2               | 320               | 21.9               | 318               | 22.1               | <b><u>318</u></b>  | <b><u>22.1</u></b> |
| 483.xalancbmk  | 179               | 38.6               | <b><u>179</u></b>  | <b><u>38.5</u></b> | 182               | 38.0               | <b><u>186</u></b> | <b><u>37.1</u></b> | 187               | 37.0               | 186                | 37.1               |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS Settings:  
Power Management = Maximum Performance (Default = Active Power Controller)  
Data Reuse = Disabled (Default = Enabled)

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter  
The Dell PowerEdge T710 and  
the Bull NovaScale T860 F2 models are electronically equivalent.  
The results have been measured on a Dell PowerEdge T710 model

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECint2006 = 40.7**

NovaScale T860 F2 (Intel Xeon X5667, 3.06 GHz)

**SPECint\_base2006 = 37.8**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Dell Inc.

**Test date:** Mar-2010

**Hardware Availability:** Mar-2010

**Software Availability:** Dec-2009

## Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

```

## Base Optimization Flags

C benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

C++ benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m64
```

```
400.perlbench: icc -m32
```

```
429.mcf: icc -m32
```

```
445.gobmk: icc -m32
```

```
464.h264ref: icc -m32
```

C++ benchmarks (except as noted below):

```
icpc -m32
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECint2006 = 40.7**

NovaScale T860 F2 (Intel Xeon X5667, 3.06 GHz)

**SPECint\_base2006 = 37.8**

CPU2006 license: 20

Test date: Mar-2010

Test sponsor: Bull SAS

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009

## Peak Compiler Invocation (Continued)

473.astar: icpc -m64

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
 401.bzip2: -DSPEC\_CPU\_LP64  
 403.gcc: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
 473.astar: -DSPEC\_CPU\_LP64  
 483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div -static(pass 2) -prof-use(pass 2)  
 -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc  
 -opt-malloc-options=3 -auto-ilp32

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
 -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2  
 -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -unroll4

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel  
 -opt-prefetch -par-schedule-static=32768 -ansi-alias

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -unroll2 -ansi-alias

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Bull SAS**

**SPECint2006 = 40.7**

NovaScale T860 F2 (Intel Xeon X5667, 3.06 GHz)

**SPECint\_base2006 = 37.8**

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** Dell Inc.

**Test date:** Mar-2010  
**Hardware Availability:** Mar-2010  
**Software Availability:** Dec-2009

## Peak Optimization Flags (Continued)

C++ benchmarks:

```

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
             -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
             -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
             -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
           -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
           -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs
           -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64

483.xalancbmk: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch
              -Wl,-z,muldefs
              -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

```

## Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 07:18:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 April 2010.