



SPEC ACCEL™ OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28


Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: May-2020

Hardware Availability: Jun-2020

Software Availability: Jun-2020





SPEC ACCEL OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28

Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: May-2020

Hardware Availability: Jun-2020

Software Availability: Jun-2020

Hardware

CPU Name: AMD EPYC 7H12
CPU Characteristics: Turbo up to 3.3 GHz
CPU MHz: 2600
CPU MHz Maximum: 3300
FPU: Integrated
CPU(s) enabled: 128 cores, 2 chips, 64 cores/chip, 2 threads/core
CPU(s) orderable: 1-2 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 512 KB I+D on chip per core
L3 Cache: 256 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC4-3200AA-R)
Disk Subsystem: 1x 480 GB 2.5" SSD
Other Hardware: None

Accelerator

Accel Model Name: Tesla V100S
Accel Vendor: NVIDIA Corporation
Accel Name: NVIDIA Tesla V100S-PCIE-32GB
Type of Accel: GPU
Accel Connection: PCIe 3.0 16x
Does Accel Use ECC: Yes
Accel Description: NVIDIA Tesla V100S-PCIE-32GB
Accel Driver: NVIDIA UNIX x86_64 Kernel Module 418.87

Software

Operating System: SUSE Linux Enterprise Server 15 SP1
4.12.14-195-default
Compiler: PGI Professional Edition Release 19.10
File System: btrfs
System State: Run level 3
Other Software: CUDA 10.1 SDK



SPEC ACCEL OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: May-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
101.tpacf	6.47	16.5	<u>6.46</u>	<u>16.6</u>	6.40	16.7						
103.stencil	<u>6.62</u>	<u>18.9</u>	6.66	18.8	6.61	18.9						
104.lbm	5.84	19.2	5.85	19.2	<u>5.84</u>	<u>19.2</u>						
110.fft	<u>6.43</u>	<u>17.3</u>	6.45	17.2	6.43	17.3						
112.spmv	18.1	8.14	<u>18.1</u>	<u>8.14</u>	18.0	8.16						
114.mriq	<u>3.38</u>	<u>32.3</u>	3.38	32.3	3.36	32.5						
116.histo	<u>35.9</u>	<u>3.18</u>	36.8	3.10	35.4	3.22						
117.bfs	<u>17.8</u>	<u>6.56</u>	17.9	6.54	17.8	6.56						
118.cutcp	<u>4.21</u>	<u>23.5</u>	4.21	23.5	4.26	23.2						
120.kmeans	<u>38.9</u>	<u>2.57</u>	38.7	2.59	40.3	2.48						
121.lavamd	4.75	22.9	<u>4.77</u>	<u>22.8</u>	4.78	22.8						
122.cfd	<u>13.3</u>	<u>9.50</u>	13.3	9.50	13.3	9.46						
123.nw	13.8	8.30	13.8	8.35	<u>13.8</u>	<u>8.34</u>						
124.hotspot	8.11	14.1	7.99	14.3	<u>8.10</u>	<u>14.1</u>						
125.lud	<u>10.8</u>	<u>11.0</u>	10.8	11.0	10.8	11.0						
126.ge	<u>5.66</u>	<u>27.4</u>	5.66	27.4	5.68	27.3						
127.srad	11.3	10.1	11.2	10.1	<u>11.3</u>	<u>10.1</u>						
128.heartwall	9.44	11.2	<u>9.46</u>	<u>11.2</u>	9.51	11.1						
140.bplustree	7.30	14.8	<u>7.30</u>	<u>14.8</u>	7.31	14.8						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Platform Notes

```
Sysinfo program /home/ACCEL1.3/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on linux-x8nq Mon May 4 13:20:04 2020
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/accel/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : AMD EPYC 7H12 64-Core Processor
```

Continued on next page



SPEC ACCEL OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28

Test sponsor: Lenovo Global Technology

Tested by: Lenovo Global Technology

Test date: May-2020

Hardware Availability: Jun-2020

Software Availability: Jun-2020

Platform Notes (Continued)

```

2 "physical id"s (chips)
128 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 64
siblings  : 64
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63
cache size : 512 KB

```

From /proc/meminfo

```

MemTotal:      528206152 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

From /etc/*release* /etc/*version*

```

os-release:
NAME="SLES"
VERSION="15-SP1"
VERSION_ID="15.1"
PRETTY_NAME="SUSE Linux Enterprise Server 15 SP1"
ID="sles"
ID_LIKE="suse"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:15:sp1"

```

uname -a:

```

Linux linux-x8nq 4.12.14-195-default #1 SMP Tue May 7 10:55:11 UTC 2019
(8fba516) x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 May 4 11:50

SPEC is set to: /home/ACCEL1.3

```

Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/sda4       btrfs    444G  153G  290G   35% /home

```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Lenovo D8E105F-1.00 03/19/2020

Memory:

Continued on next page



SPEC ACCEL OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: May-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Platform Notes (Continued)

16x Samsung M393A4G43AB3-CWE 32 kB 2 rank 3200 MT/s
16x Unknown Unknown

(End of data from sysinfo program)

Base Runtime Environment

C benchmarks:

OpenCL Platform: NVIDIA CUDA, OpenCL 1.2 CUDA 10.1.236
OpenCL Device #0: Graphics Device, v 418.87.00

C++ benchmarks:

OpenCL Platform: NVIDIA CUDA, OpenCL 1.2 CUDA 10.1.236
OpenCL Device #0: Graphics Device, v 418.87.00

Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgc++

Base Portability Flags

116.histo: -DSPEC_LOCAL_MEMORY_HEADROOM=1
118.cutcp: -D__GNUC__

Base Optimization Flags

C benchmarks:

-fast -Mfprelaxed

C++ benchmarks:

-fast -Mfprelaxed



SPEC ACCEL OCL Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology
NVIDIA Tesla V100S-PCIE-32GB
ThinkSystem SR665

SPECaccel_ocl_peak = Not Run

SPECaccel_ocl_base = 12.2

ACCEL license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: May-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Base Other Flags

C benchmarks:

```
-I/usr/local/cuda-10.1/targets/x86_64-linux/include  
-L/usr/local/cuda-10.1/lib64 -lOpenCL
```

C++ benchmarks:

```
-I/usr/local/cuda-10.1/targets/x86_64-linux/include  
-L/usr/local/cuda-10.1/lib64 -lOpenCL
```

The flags file that was used to format this result can be browsed at

https://www.spec.org/accel/flags/PGI_flags.html

You can also download the XML flags source by saving the following link:

https://www.spec.org/accel/flags/PGI_flags.xml

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.3.
Report generated on Thu May 21 10:55:37 2020 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 20 May 2020.