



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Ri-2  
(Intel Xeon processor X5355)

SPECfp®\_rate2006 = 58.1

SPECfp\_rate\_base2006 = 56.3

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: Jan-2007

Software Availability: Apr-2007



### Hardware

CPU Name: Intel Xeon X5355  
 CPU Characteristics: 2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus  
 CPU MHz: 2666  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86\_64  
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package-ID: l\_cc\_c\_9.1.049  
 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package ID: l\_fc\_c\_9.1.045  
 Auto Parallel: No  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Ri-2  
(Intel Xeon processor X5355)

SPECfp\_rate2006 = 58.1

SPECfp\_rate\_base2006 = 56.3

CPU2006 license: 9006  
Test sponsor: NEC Corporation  
Tested by: NEC Corporation

Test date: Jun-2007  
Hardware Availability: Jan-2007  
Software Availability: Apr-2007

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8x2 GB DDR2 5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
Other Hardware: None

System State: Multiuser, Runlevel 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3416	31.8	3414	31.8	<b>3416</b>	<b>31.8</b>	8	3416	31.8	3414	31.8	<b>3416</b>	<b>31.8</b>
416.gamess	8	<b>1076</b>	<b>146</b>	1074	146	1076	146	8	<b>1076</b>	<b>146</b>	1074	146	1076	146
433.milc	8	<b>3498</b>	<b>21.0</b>	3494	21.0	3498	21.0	8	3695	19.9	3697	19.9	<b>3696</b>	<b>19.9</b>
434.zeusmp	8	1153	63.1	<b>1162</b>	<b>62.7</b>	1162	62.7	8	1163	62.6	1156	63.0	<b>1156</b>	<b>63.0</b>
435.gromacs	8	457	125	450	127	<b>453</b>	<b>126</b>	8	438	130	441	129	<b>439</b>	<b>130</b>
436.cactusADM	8	1383	69.1	1368	69.9	<b>1372</b>	<b>69.7</b>	8	1383	69.1	1368	69.9	<b>1372</b>	<b>69.7</b>
437.leslie3d	8	<b>3241</b>	<b>23.2</b>	3269	23.0	3240	23.2	8	<b>3241</b>	<b>23.2</b>	3269	23.0	3240	23.2
444.namd	8	577	111	<b>577</b>	<b>111</b>	576	111	8	577	111	<b>577</b>	<b>111</b>	576	111
447.dealII	8	746	123	<b>733</b>	<b>125</b>	726	126	8	<b>723</b>	<b>127</b>	717	128	743	123
450.soplex	8	2330	28.6	<b>2333</b>	<b>28.6</b>	2334	28.6	8	2127	31.4	2124	31.4	<b>2126</b>	<b>31.4</b>
453.povray	8	292	146	295	144	<b>294</b>	<b>145</b>	8	220	193	<b>221</b>	<b>192</b>	222	192
454.calculix	8	629	105	<b>632</b>	<b>104</b>	634	104	8	623	106	<b>620</b>	<b>106</b>	619	107
459.GemsFDTD	8	4058	20.9	<b>4057</b>	<b>20.9</b>	4054	20.9	8	4058	20.9	<b>4057</b>	<b>20.9</b>	4054	20.9
465.tonto	8	1020	77.2	<b>1014</b>	<b>77.7</b>	1002	78.5	8	986	79.9	993	79.3	<b>990</b>	<b>79.5</b>
470.lbm	8	<b>4569</b>	<b>24.1</b>	4570	24.1	4567	24.1	8	4293	25.6	4297	25.6	<b>4293</b>	<b>25.6</b>
481.wrf	8	1952	45.8	<b>1949</b>	<b>45.9</b>	1948	45.9	8	1952	45.8	<b>1949</b>	<b>45.9</b>	1948	45.9
482.sphinx3	8	3685	42.3	3694	42.2	<b>3687</b>	<b>42.3</b>	8	3404	45.8	<b>3405</b>	<b>45.8</b>	3407	45.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs

## General Notes

The system bus runs at 1333 MHz  
All binaries were built with 64-bit Intel compiler except:  
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with  
32-bit Intel compiler by changing the path for include and library files.

The Express5800/120Rg-1 and the Express5800/120Ri-2 models are  
electronically equivalent.  
The results have been measured on a Express5800/120Ri-2 model.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Ri-2  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 58.1**

**SPECfp\_rate\_base2006 = 56.3**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jun-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Ri-2  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 58.1**

**SPECfp\_rate\_base2006 = 56.3**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jun-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.049/bin/icc -I/opt/intel/cc/9.1.049/include  
-L/opt/intel/cc/9.1.049/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.049/bin/icpc  
-I/opt/intel/cc/9.1.049/include -L/opt/intel/cc/9.1.049/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.045/bin/ifort  
-I/opt/intel/fc/9.1.045/include -L/opt/intel/fc/9.1.045/lib
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast
```

```
470.lbm: Same as 433.milc
```

```
482.sphinx3: -fast
```

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Ri-2  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 58.1**

**SPECfp\_rate\_base2006 = 56.3**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jun-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

### Benchmarks using both Fortran and C:

435.gromacs: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.20090714.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 13:01:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 10 July 2007.