



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

**SPECfp®2006 = 16.7**

Intel DQ965GF motherboard (Intel Core 2 Duo E6700)

**SPECfp\_base2006 = 16.1**

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2007

Hardware Availability: Aug-2006

Software Availability: Aug-2006



### Hardware

CPU Name: Intel Core 2 Duo E6700  
 CPU Characteristics: 2.67 GHz, 1066 MHz bus  
 CPU MHz: 2667  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: Windows Vista32 Ultimate  
 Compiler: Intel C++ Compiler for IA32 version 10.0  
 Build 20070426 Package ID: W\_CC\_P\_10.0.025  
 Intel Fortran Compiler for IA32 version 10.0  
 Build 20070426 Package ID: W\_FC\_P\_10.0.025  
 Microsoft Visual Studio .Net 2003 (for libraries)  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp2006 = **16.7**

Intel DQ965GF motherboard (Intel Core 2 Duo E6700)

SPECfp\_base2006 = **16.1**

CPU2006 license: 13

Test date: Jun-2007

Test sponsor: Intel Corporation

Hardware Availability: Aug-2006

Tested by: Intel Corporation

Software Availability: Aug-2006

L3 Cache: None  
 Other Cache: None  
 Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)  
 Disk Subsystem: Seagate ST3320620AS 320GB Barracuda 7200.10 NCQ SATA II  
 Other Hardware: None

Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: SmartHeap Library Version 8.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	596	22.8	<b>595</b>	<b>22.8</b>	594	22.9	596	22.8	594	22.9	<b>595</b>	<b>22.8</b>
416.gamess	1355	14.4	<b>1355</b>	<b>14.4</b>	1356	14.4	1339	14.6	<b>1341</b>	<b>14.6</b>	1341	14.6
433.milc	784	11.7	<b>784</b>	<b>11.7</b>	785	11.7	780	11.8	778	11.8	<b>779</b>	<b>11.8</b>
434.zeusmp	571	15.9	<b>571</b>	<b>15.9</b>	571	15.9	533	17.1	<b>533</b>	<b>17.1</b>	533	17.1
435.gromacs	463	15.4	463	15.4	<b>463</b>	<b>15.4</b>	453	15.8	<b>453</b>	<b>15.8</b>	454	15.7
436.cactusADM	652	18.3	<b>652</b>	<b>18.3</b>	652	18.3	652	18.3	<b>652</b>	<b>18.3</b>	652	18.3
437.leslie3d	639	14.7	<b>640</b>	<b>14.7</b>	640	14.7	637	14.8	638	14.7	<b>637</b>	<b>14.8</b>
444.namd	580	13.8	<b>580</b>	<b>13.8</b>	580	13.8	579	13.9	<b>579</b>	<b>13.9</b>	579	13.8
447.dealII	602	19.0	602	19.0	<b>602</b>	<b>19.0</b>	<b>539</b>	<b>21.2</b>	539	21.2	539	21.2
450.soplex	557	15.0	<b>558</b>	<b>15.0</b>	558	15.0	561	14.9	560	14.9	<b>561</b>	<b>14.9</b>
453.povray	279	19.1	<b>279</b>	<b>19.1</b>	279	19.1	<b>216</b>	<b>24.6</b>	216	24.6	216	24.6
454.calculix	677	12.2	677	12.2	<b>677</b>	<b>12.2</b>	677	12.2	<b>677</b>	<b>12.2</b>	677	12.2
459.GemsFDTD	841	12.6	<b>841</b>	<b>12.6</b>	840	12.6	841	12.6	<b>841</b>	<b>12.6</b>	840	12.6
465.tonto	667	14.8	<b>667</b>	<b>14.8</b>	666	14.8	<b>652</b>	<b>15.1</b>	652	15.1	652	15.1
470.lbm	805	17.1	<b>805</b>	<b>17.1</b>	805	17.1	741	18.5	<b>742</b>	<b>18.5</b>	742	18.5
481.wrf	<b>592</b>	<b>18.9</b>	592	18.9	592	18.9	592	18.9	593	18.8	<b>593</b>	<b>18.9</b>
482.sphinx3	825	23.6	<b>825</b>	<b>23.6</b>	824	23.7	821	23.8	822	23.7	<b>821</b>	<b>23.7</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply  
 Product description located as of 7/2007:  
<http://www.intel.com/products/motherboard/DQ965GF/index.htm>  
 The system bus runs at 1066 MHz  
 System was configured with integrated graphics card  
 Binaries were built on Windows XP Professional SP2 with 4GB of RAM and /3GB boot switch

## Base Compiler Invocation

C benchmarks:  
 icl -Qvc7.1 -Qc99

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 16.7

Intel DQ965GF motherboard (Intel Core 2 Duo E6700)

SPECfp\_base2006 = 16.1

CPU2006 license: 13

Test date: Jun-2007

Test sponsor: Intel Corporation

Hardware Availability: Aug-2006

Tested by: Intel Corporation

Software Availability: Aug-2006

## Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc7.1

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort

## Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
-DBOOST\_NO\_INTRINSIC\_WCHAR\_T  
453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Base Optimization Flags

C benchmarks:

-fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx\_features /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

-fast /F950000000

Benchmarks using both Fortran and C:

-fast /F950000000

## Peak Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Fortran benchmarks:

ifort

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 16.7

Intel DQ965GF motherboard (Intel Core 2 Duo E6700)

SPECfp\_base2006 = 16.1

CPU2006 license: 13

Test date: Jun-2007

Test sponsor: Intel Corporation

Hardware Availability: Aug-2006

Tested by: Intel Corporation

Software Availability: Aug-2006

## Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:  
icl -Qvc7.1 -Qc99 ifort

## Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
-DBOOST\_NO\_INTRINSIC\_WCHAR\_T  
453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Peak Optimization Flags

C benchmarks:

433.milc: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2 -Oa  
/F950000000 shlw32m.lib -link /FORCE:MULTIPLE

470.lbm: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2  
-Qscalar-rep- -Qprefetch /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

482.sphinx3: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2  
/F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:

444.namd: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Oa  
-Qcxx\_features /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

447.dealII: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qprefetch  
-Qcxx\_features /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

450.soplex: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qcxx\_features  
/F950000000 shlw32m.lib -link /FORCE:MULTIPLE

453.povray: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qansi-alias  
-Qcxx\_features /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 16.7

Intel DQ965GF motherboard (Intel Core 2 Duo E6700)

SPECfp\_base2006 = 16.1

CPU2006 license: 13

Test date: Jun-2007

Test sponsor: Intel Corporation

Hardware Availability: Aug-2006

Tested by: Intel Corporation

Software Availability: Aug-2006

## Peak Optimization Flags (Continued)

410.bwaves: -fast /F950000000

416.gamess: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2 -Ob0  
-Qansi-alias -Qscalar-rep- /F950000000

434.zeusmp: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -QxT -O2 -Qprec\_div-  
-Qunroll10 -Qscalar-rep- /F950000000

437.leslie3d: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F950000000

459.GemsFDTD: basepeak = yes

465.tonto: Same as 437.leslie3d

Benchmarks using both Fortran and C:

435.gromacs: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Oa  
/F950000000

436.cactusADM: basepeak = yes

454.calculix: -fast /F950000000

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 12:47:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 August 2007.