



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®2006 = 20.9

IBM System x3550 (Intel Xeon 5160)

SPECint\_base2006 = 19.0

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Jul-2006

Software Availability: Jul-2007



## Hardware

CPU Name: Intel Xeon 5160  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2GB DDR2-5300F ECC)  
 Disk Subsystem: 1 x 36GB SAS, 15000RPM  
 Other Hardware: None

## Software

Operating System: SLES 10 (x86\_64), 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler for Linux version 10.0  
 Build 20070426 Package ID: 1\_cc\_p\_10.0.023  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap 8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.9

IBM System x3550 (Intel Xeon 5160)

SPECint\_base2006 = 19.0

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Jul-2007  
Hardware Availability: Jul-2006  
Software Availability: Jul-2007

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	484	20.2	487	20.0	<b>484</b>	<b>20.2</b>	406	24.1	412	23.7	<b>407</b>	<b>24.0</b>
401.bzip2	610	15.8	<b>612</b>	<b>15.8</b>	612	15.8	571	16.9	575	16.8	<b>572</b>	<b>16.9</b>
403.gcc	<b>447</b>	<b>18.0</b>	447	18.0	447	18.0	<b>447</b>	<b>18.0</b>	447	18.0	447	18.0
429.mcf	484	18.9	<b>476</b>	<b>19.2</b>	475	19.2	454	20.1	449	20.3	<b>452</b>	<b>20.2</b>
445.gobmk	536	19.6	537	19.5	<b>537</b>	<b>19.5</b>	<b>491</b>	<b>21.4</b>	490	21.4	491	21.4
456.hmmmer	<b>593</b>	<b>15.7</b>	593	15.7	594	15.7	<b>466</b>	<b>20.0</b>	466	20.0	466	20.0
458.sjeng	689	17.6	<b>690</b>	<b>17.5</b>	695	17.4	613	19.8	<b>614</b>	<b>19.7</b>	614	19.7
462.libquantum	821	25.2	841	24.7	<b>840</b>	<b>24.7</b>	747	27.7	698	29.7	<b>698</b>	<b>29.7</b>
464.h264ref	<b>714</b>	<b>31.0</b>	713	31.0	715	31.0	676	32.7	678	32.6	<b>676</b>	<b>32.7</b>
471.omnetpp	<b>462</b>	<b>13.5</b>	463	13.5	460	13.6	426	14.7	<b>426</b>	<b>14.7</b>	433	14.4
473.astar	498	14.1	<b>493</b>	<b>14.2</b>	490	14.3	449	15.6	454	15.5	<b>451</b>	<b>15.6</b>
483.xalancbmk	<b>280</b>	<b>24.6</b>	279	24.7	280	24.6	<b>280</b>	<b>24.6</b>	279	24.7	280	24.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/cpu2006.1.0/lib -lsmartheap



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.9

IBM System x3550 (Intel Xeon 5160)

SPECint\_base2006 = 19.0

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Jul-2006

Software Availability: Jul-2007

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc  
-L/opt/intel/cce/10.0.023/lib  
-I/opt/intel/cce/10.0.023/include

456.hmmer: /opt/intel/cce/10.0.023/bin/icc  
-L/opt/intel/cce/10.0.023/lib  
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast

403.gcc: basepeak = yes

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec\_div -ansi-alias

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	SPECint2006 =	20.9
IBM System x3550 (Intel Xeon 5160)	SPECint_base2006 =	19.0

CPU2006 license: 11	Test date: Jul-2007
Test sponsor: IBM Corporation	Hardware Availability: Jul-2006
Tested by: IBM Corporation	Software Availability: Jul-2007

## Peak Optimization Flags (Continued)

456.hmmcr: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -Ob0  
-prefetch -opt-streaming-stores always

464.h264ref: Same as 456.hmmcr

### C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec\_div -ansi-alias -Wl,-z,muldefs  
-L/spec/cpu2006.1.0/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

## Peak Other Flags

### C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.44.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.44.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 12:32:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 23 August 2007.