



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint®_rate2006 = 60.1

ProLiant BL480c
(3.0 GHz, Intel Xeon processor X5365)

SPECint_rate_base2006 = 52.2

CPU2006 license: 3


Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5365
 CPU Characteristics: 3.0 GHz, 2x4 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F CL5)
 Disk Subsystem: 1x72 GB 15 K SAS
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP1
 kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler for Linux32 and Linux64
 version 10.1
 Build 20070725
 Auto Parallel: Yes
 File System: ext2
 System State: Multi-user run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1
 binutils-2.17.50



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 60.1

ProLiant BL480c
(3.0 GHz, Intel Xeon processor X5365)

SPECint_rate_base2006 = 52.2

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	555	70.5	554	70.6	554	70.5	4	459	85.1	455	85.9	454	86.1
401.bzip2	4	906	42.6	906	42.6	926	41.7	4	866	44.6	873	44.2	872	44.3
403.gcc	4	649	49.6	652	49.4	649	49.6	4	660	48.8	650	49.5	651	49.4
429.mcf	4	893	40.9	895	40.8	893	40.9	4	886	41.2	887	41.1	888	41.1
445.gobmk	4	565	74.2	569	73.7	573	73.2	4	520	80.6	520	80.7	524	80.0
456.hammer	4	747	50.0	755	49.4	742	50.3	4	447	83.5	457	81.6	446	83.7
458.sjeng	4	706	68.6	706	68.5	697	69.4	4	638	75.9	640	75.6	639	75.7
462.libquantum	4	2728	30.4	2728	30.4	2723	30.4	1	387	53.6	389	53.3	387	53.6
464.h264ref	4	788	112	787	112	786	113	4	733	121	729	121	723	122
471.omnetpp	4	786	31.8	790	31.7	787	31.8	4	769	32.5	770	32.5	769	32.5
473.astar	4	740	37.9	742	37.9	740	38.0	4	691	40.6	693	40.5	691	40.6
483.xalancbmk	4	422	65.5	423	65.3	422	65.4	4	422	65.5	423	65.3	422	65.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M

Platform Notes

BIOS configuration:
Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 60.1

ProLiant BL480c
(3.0 GHz, Intel Xeon processor X5365)

SPECint_rate_base2006 = 52.2

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 60.1

ProLiant BL480c
(3.0 GHz, Intel Xeon processor X5365)

SPECint_rate_base2006 = 52.2

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 60.1

ProLiant BL480c
(3.0 GHz, Intel Xeon processor X5365)

SPECint_rate_base2006 = 52.2

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-flags.20090714.01.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:36:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 18 September 2007.