



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL185 G5
(3.0 GHz AMD Opteron 2222)

SPECint®2006 = 16.1

SPECint_base2006 = 14.7

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Dec-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name:	AMD Opteron 2222
CPU Characteristics:	
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	32 GB (8x4 GB PC2-5300P CL5)
Disk Subsystem:	1x146 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1
Compiler:	Kernel 2.6.16.46-0.12-smp
	The Portland Group (PGI)
	PGI pgcc 7.1-1 C Compiler
	PGI pgCC 7.1-1 C++ Compiler
Auto Parallel:	QLogic PathScale Compiler Suite, Release 3.0
File System:	No
System State:	ext2
Base Pointers:	Multi-user run level 3
Peak Pointers:	32/64-bit
Other Software:	32/64-bit
	MicroQuill SmartHeap Library 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL185 G5
(3.0 GHz AMD Opteron 2222)

SPECint2006 = 16.1

SPECint_base2006 = 14.7

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	774	12.6	771	12.7	775	12.6	591	16.5	589	16.6	589	16.6
401.bzip2	850	11.3	850	11.4	850	11.3	830	11.6	830	11.6	830	11.6
403.gcc	764	10.5	763	10.5	763	10.6	636	12.7	637	12.6	637	12.6
429.mcf	624	14.6	627	14.5	636	14.3	498	18.3	505	18.1	503	18.1
445.gobmk	699	15.0	696	15.1	696	15.1	585	17.9	583	18.0	583	18.0
456.hmmer	470	19.9	466	20.0	475	19.7	438	21.3	437	21.3	440	21.2
458.sjeng	848	14.3	848	14.3	849	14.3	812	14.9	812	14.9	812	14.9
462.libquantum	756	27.4	757	27.4	756	27.4	703	29.5	703	29.5	703	29.5
464.h264ref	1016	21.8	1018	21.7	1003	22.1	965	22.9	943	23.5	958	23.1
471.omnetpp	571	10.9	575	10.9	575	10.9	571	10.9	575	10.9	575	10.9
473.astar	657	10.7	661	10.6	665	10.6	657	10.7	661	10.6	665	10.6
483.xalancbmk	446	15.5	447	15.5	447	15.5	452	15.3	451	15.3	451	15.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Environment stack size set to 'unlimited'
ulimit -l set to 1048576
'numactl' was used to bind copies to the cores
Set vm/nr_hugepages=1024 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
```

Base Compiler Invocation

C benchmarks:
 pgcc

C++ benchmarks:
 pgcpp

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL185 G5
(3.0 GHz AMD Opteron 2222)

SPECint2006 = 16.1

SPECint_base2006 = 14.7

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Dec-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mipa=noarg -Mfprelaxed
-Msmartralloc=huge:840 -tp k8-64 -Bstatic_pgi

C++ benchmarks:

-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:448
--zc_eh -tp k8-32 -Bstatic_pgi
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w

Peak Compiler Invocation

C benchmarks (except as noted below):

pgcc

400.perlbench: pathcc

403.gcc: pathcc

445.gobmk: pathcc

464.h264ref: pathcc

C++ benchmarks:

pgcpp



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL185 G5
(3.0 GHz AMD Opteron 2222)

SPECint2006 = 16.1

SPECint_base2006 = 14.7

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Dec-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
 401.bzip2: -DSPEC_CPU_LP64
 445.gobmk: -DSPEC_CPU_LP64
 456.hmmr: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 464.h264ref: -DSPEC_CPU_LP64
 483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
  -LNO:opt=0

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4
  -Msmartralloc=huge:448 -tp k8-64 -Bstatic_pgi

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
  -OPT:Ofast

429.mcf: -fastsse -Mipa=fast -Mipa=inline -Msmartralloc=huge:420
  -tp k8-32 -Bstatic_pgi

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
  -OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
  -WOPT:retype_expr=on

456.hmmr: -fast -Msmartralloc=huge:448 -Mfprelaxed -Msafepr
  -Mipa=const -Mipa=ptr -Mipa=arg -tp k8-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
  -Mipa=noarg(pass 2) -Mpfo(pass 2) -fast
  -Msmartralloc=huge:448 -Mfprelaxed -tp k8-64 -Bstatic_pgi

462.libquantum: -fast -Mfprelaxed -Msmartralloc=huge:448 -Munroll=m:4
  -Mipa=fast -Mipa=inline -Mipa=noarg -Bstatic_pgi

464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
  -IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0
```

C++ benchmarks:

```
471.omnetpp: basepeak = yes

473.astar: basepeak = yes
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL185 G5
(3.0 GHz AMD Opteron 2222)

SPECint2006 = 16.1

SPECint_base2006 = 14.7

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

```
483.xalancbmk: -fastsse -O4 -Mipa=fast -Mipa=inline -Mfprelaxed  
-Msmartralloc=huge:420 --zc_eh -tp k8-32 -Bstatic_pgi  
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap
```

Peak Other Flags

C benchmarks (except as noted below):

-w

400.perlbench: No flags used

403.gcc: No flags used

445.gobmk: No flags used

464.h264ref: No flags used

C++ benchmarks:

-w

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/hp-ppi710_ps30_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/hp-ppi710_ps30_flags.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 15:13:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 14 January 2008.