



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp®2006 = 24.3

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = 20.8

CPU2006 license: 22


Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5260
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smpp
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64, version 10.1, Build 20070913
 Auto Parallel: Yes
 File System: ext2
 System State: Multi-User Run Level 3
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = **24.3**

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = **20.8**

CPU2006 license: 22

Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL 5-5-5, ECC)
Disk Subsystem: 1x SAS, 73 GB, 15000 rpm
Other Hardware: None

Other Software: binutils-2.17.50.0.5-0.1.x86_64

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---------------|------------|-------------|------------|-------------|-------------|-------------|------------|-------------|------------|-------------|------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 406 | 33.5 | 406 | 33.5 | 406 | 33.4 | 393 | 34.5 | 395 | 34.4 | 393 | 34.5 |
| 416.gamess | 833 | 23.5 | 821 | 23.8 | 824 | 23.8 | 789 | 24.8 | 784 | 25.0 | 786 | 24.9 |
| 433.milc | 811 | 11.3 | 810 | 11.3 | 808 | 11.4 | 829 | 11.1 | 827 | 11.1 | 828 | 11.1 |
| 434.zeusmp | 503 | 18.1 | 503 | 18.1 | 503 | 18.1 | 519 | 17.5 | 517 | 17.6 | 518 | 17.6 |
| 435.gromacs | 332 | 21.5 | 333 | 21.5 | 330 | 21.6 | 328 | 21.7 | 328 | 21.7 | 328 | 21.7 |
| 436.cactusADM | 316 | 37.8 | 316 | 37.8 | 317 | 37.6 | 173 | 69.1 | 174 | 68.6 | 176 | 68.0 |
| 437.leslie3d | 476 | 19.7 | 479 | 19.6 | 477 | 19.7 | 476 | 19.7 | 479 | 19.6 | 477 | 19.7 |
| 444.namd | 454 | 17.7 | 454 | 17.6 | 454 | 17.7 | 452 | 17.7 | 453 | 17.7 | 453 | 17.7 |
| 447.dealII | 373 | 30.7 | 374 | 30.6 | 373 | 30.6 | 354 | 32.3 | 354 | 32.3 | 354 | 32.3 |
| 450.soplex | 575 | 14.5 | 576 | 14.5 | 576 | 14.5 | 515 | 16.2 | 514 | 16.2 | 517 | 16.1 |
| 453.povray | 190 | 28.0 | 195 | 27.3 | 192 | 27.7 | 160 | 33.2 | 161 | 33.0 | 160 | 33.2 |
| 454.calculix | 463 | 17.8 | 463 | 17.8 | 463 | 17.8 | 319 | 25.8 | 319 | 25.9 | 318 | 26.0 |
| 459.GemsFDTD | 523 | 20.3 | 524 | 20.3 | 524 | 20.3 | 516 | 20.6 | 516 | 20.6 | 516 | 20.6 |
| 465.tonto | 410 | 24.0 | 411 | 23.9 | 414 | 23.8 | 392 | 25.1 | 393 | 25.0 | 394 | 25.0 |
| 470.lbm | 1747 | 7.87 | 1755 | 7.83 | 1753 | 7.84 | 540 | 25.4 | 539 | 25.5 | 540 | 25.4 |
| 481.wrf | 467 | 23.9 | 467 | 23.9 | 467 | 23.9 | 476 | 23.5 | 475 | 23.5 | 476 | 23.5 |
| 482.sphinx3 | 683 | 28.5 | 666 | 29.3 | 692 | 28.2 | 643 | 30.3 | 638 | 30.6 | 651 | 29.9 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores (default)

Platform Notes

BIOS configuration:
Hardware Prefetch = Enable, Adjacent Sector Prefetch = Enable

General Notes

All binaries were built with 64-bit Intel compiler except:
450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 24.3

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = 20.8

CPU2006 license: 22

Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

General Notes (Continued)

for include and library files.

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:
-fast -parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 24.3

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = 20.8

CPU2006 license: 22

Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Base Optimization Flags (Continued)

C++ benchmarks:

-fast -parallel

Fortran benchmarks:

-fast -parallel

Benchmarks using both Fortran and C:

-fast -parallel

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 24.3

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = 20.8

CPU2006 license: 22

Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp2006 = 24.3

PRIMERGY RX200 S4, Intel Xeon X5260, 3.33 GHz

SPECfp_base2006 = 20.8

CPU2006 license: 22

Test date: Jul-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:05:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 September 2008.