



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

## SPECint®\_rate2006 = Not Run

### PRIMERGY RX300 S4, Intel Xeon X5470, 3.33 GHz

## SPECint\_rate\_base2006 = 139

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



### Hardware

CPU Name: Intel Xeon X5470  
 CPU Characteristics: 1333 MHz system bus  
 CPU MHz: 3333  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
 Disk Subsystem: 1x SAS, 73 GB, 15000 rpm  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042  
 Auto Parallel: No  
 File System: ext3  
 System State: Multi-User Run Level 3  
 Base Pointers: 32-bit  
 Peak Pointers: Not Applicable  
 Other Software: Microquill SmartHeap Library, Version 8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

SPECint\_rate2006 = Not Run

PRIMERGY RX300 S4, Intel Xeon X5470, 3.33 GHz

SPECint\_rate\_base2006 = 139

CPU2006 license: 22

Test date: Aug-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Oct-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2008

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	454	172	448	174	<b><u>454</u></b>	<b><u>172</u></b>							
401.bzip2	8	684	113	<b><u>691</u></b>	<b><u>112</u></b>	697	111							
403.gcc	8	601	107	604	107	<b><u>602</u></b>	<b><u>107</u></b>							
429.mcf	8	674	108	675	108	<b><u>675</u></b>	<b><u>108</u></b>							
445.gobmk	8	511	164	507	166	<b><u>508</u></b>	<b><u>165</u></b>							
456.hammer	8	<b><u>448</u></b>	<b><u>167</u></b>	446	167	448	167							
458.sjeng	8	<b><u>560</u></b>	<b><u>173</u></b>	560	173	561	172							
462.libquantum	8	863	192	<b><u>860</u></b>	<b><u>193</u></b>	859	193							
464.h264ref	8	607	292	604	293	<b><u>605</u></b>	<b><u>293</u></b>							
471.omnetpp	8	668	74.9	666	75.1	<b><u>667</u></b>	<b><u>75.0</u></b>							
473.astar	8	<b><u>646</u></b>	<b><u>86.9</u></b>	648	86.7	646	87.0							
483.xalancbmk	8	<b><u>411</u></b>	<b><u>134</u></b>	412	134	411	134							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS configuration:  
Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable  
Memory Throttling = Enable

## General Notes

For information about Fujitsu Siemens Computers please see:  
<http://www.fujitsu-siemens.com>

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint\_rate2006 = Not Run

PRIMERGY RX300 S4, Intel Xeon X5470, 3.33 GHz

SPECint\_rate\_base2006 = 139

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 19:32:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 16 September 2008.