



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9750)

SPECint®_rate2006 = 43.3

SPECint_rate_base2006 = 42.2

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Apr-2008

Software Availability: Nov-2008



Hardware

CPU Name: AMD Phenom X4 9750
 CPU Characteristics:
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 2 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (4x1GB DDR2-800 CL5)
 Disk Subsystem: Seagate 320 GB SATA, 7200RPM
 Other Hardware: None

Software

Operating System: Windows Vista Ultimate w/ SP1 (64-bit)
 Compiler: Intel C++ Compiler Professional 11.0 for IA32
 Build 20080930 Package ID: w_cproc_p_11.0.054
 Microsoft Visual Studio 2008 (for libraries)
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: SmartHeap Library Version 8.1 from
<http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9750)

SPECint_rate2006 = 43.3

SPECint_rate_base2006 = 42.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Apr-2008

Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	765	51.2	767	50.8	766	50.8	4	580	67.6	582	67.2	583	67.2
401.bzip2	4	1195	32.4	1190	32.4	1189	32.4	4	1203	32.0	1198	32.4	1195	32.4
403.gcc	4	774	41.6	762	42.4	766	42.0	4	742	43.2	744	43.2	746	43.2
429.mcf	4	1185	30.8	1187	30.8	1185	30.8	4	1182	30.8	1186	30.8	1185	30.8
445.gobmk	4	688	60.8	689	60.8	688	60.8	4	639	65.6	639	65.6	640	65.6
456.hammer	4	1976	18.8	1989	18.8	1982	18.8	4	2017	18.4	2019	18.4	2012	18.4
458.sjeng	4	962	50.4	962	50.4	963	50.4	4	884	54.8	884	54.8	884	54.8
462.libquantum	4	1120	74.0	1121	74.0	1121	74.0	1	384	54.0	385	53.9	384	54.0
464.h264ref	4	1126	78.4	1126	78.4	1126	78.8	4	1059	83.6	1059	83.6	1060	83.6
471.omnetpp	4	817	30.4	817	30.4	817	30.4	4	759	32.8	759	32.8	758	32.8
473.astar	4	868	32.4	868	32.4	867	32.4	4	831	34.0	830	34.0	830	34.0
483.xalancbmk	4	605	45.6	606	45.6	605	45.6	4	605	45.6	606	45.6	605	45.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Binaries were built on Windows Vista Ultimate (32-bit)
OMP_NUM_THREADS set to number of logical processors as seen by the OS
KMP_AFFINITY set to physical,0
submit disabled for 462.libquantum peak

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qc99

C++ benchmarks:
icl -Qvc9

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9750)

SPECint_rate2006 = 43.3

SPECint_rate_base2006 = 42.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Apr-2008

Software Availability: Nov-2008

Base Portability Flags (Continued)

483.xalanbmk: -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

C++ benchmarks:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qc99

C++ benchmarks:

icl -Qvc9

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

483.xalanbmk: -Qoption,cpp,--no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 3



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9750)

SPECint_rate2006 = 43.3

SPECint_rate_base2006 = 42.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Apr-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

401.bzip2: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
/F512000000

403.gcc: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
/F512000000

445.gobmk: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

458.sjeng: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 /F512000000

462.libquantum: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
-Qparallel -Qpar-runtime-control -Qvec-guard-write
/F512000000

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

473.astar: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=routine /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9750)

SPECint_rate2006 = 43.3

SPECint_rate_base2006 = 42.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Apr-2008

Software Availability: Nov-2008

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 01:05:19 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 June 2009.