



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp®\_rate2006 = 188**

**SPECfp\_rate\_base2006 = 184**

**CPU2006 license:** 9019


**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011



### Hardware

CPU Name: Intel Xeon E5640  
CPU Characteristics: Intel Turbo Boost Technology up to 2.93 GHz  
CPU MHz: 2667  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64) with SP1, Kernel 2.6.32.12-0.7-default  
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp\_rate2006 = 188**

**SPECfp\_rate\_base2006 = 184**

**CPU2006 license:** 9019

**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011

L3 Cache: 12 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 48 GB (12 x 4 GB 2Rx4 PC3L-10600R-9, ECC)  
 Disk Subsystem: 73 GB SAS, 15K RPM  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Binaries compiled on RHEL5.5 with binutils-2.17.50.0.6-14.el5

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	1340	162	1341	162	<b>1341</b>	<b>162</b>	8	656	166	<b>656</b>	<b>166</b>	656	166
416.gamess	16	<b>1641</b>	<b>191</b>	1638	191	1702	184	8	<b>847</b>	<b>185</b>	854	183	846	185
433.milc	16	842	174	<b>843</b>	<b>174</b>	844	174	16	832	176	<b>833</b>	<b>176</b>	834	176
434.zeusmp	16	670	217	686	212	<b>685</b>	<b>212</b>	16	670	217	686	212	<b>685</b>	<b>212</b>
435.gromacs	16	643	178	652	175	<b>651</b>	<b>176</b>	16	650	176	<b>650</b>	<b>176</b>	657	174
436.cactusADM	16	901	212	<b>904</b>	<b>212</b>	906	211	16	901	212	<b>904</b>	<b>212</b>	906	211
437.leslie3d	16	1280	118	<b>1278</b>	<b>118</b>	1276	118	8	612	123	<b>610</b>	<b>123</b>	609	124
444.namd	16	779	165	<b>779</b>	<b>165</b>	781	164	16	768	167	<b>768</b>	<b>167</b>	771	166
447.dealII	16	627	292	<b>628</b>	<b>291</b>	633	289	16	<b>670</b>	<b>273</b>	670	273	670	273
450.soplex	16	1032	129	1031	129	<b>1032</b>	<b>129</b>	8	482	138	<b>481</b>	<b>139</b>	481	139
453.povray	16	339	251	<b>338</b>	<b>252</b>	336	253	16	<b>288</b>	<b>296</b>	290	294	284	299
454.calculix	16	605	218	<b>606</b>	<b>218</b>	606	218	16	605	218	<b>606</b>	<b>218</b>	606	218
459.GemsFDTD	16	<b>1536</b>	<b>111</b>	1535	111	1538	110	16	<b>1536</b>	<b>111</b>	1535	111	1538	110
465.tonto	16	770	205	765	206	<b>767</b>	<b>205</b>	16	760	207	<b>754</b>	<b>209</b>	740	213
470.lbm	16	1019	216	<b>1019</b>	<b>216</b>	1019	216	8	445	247	<b>445</b>	<b>247</b>	446	247
481.wrf	16	911	196	909	197	<b>910</b>	<b>196</b>	16	911	196	909	197	<b>910</b>	<b>196</b>
482.sphinx3	16	1686	185	<b>1688</b>	<b>185</b>	1692	184	16	1614	193	<b>1614</b>	<b>193</b>	1616	193

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores

## Operating System Notes

ulimit -s unlimited was used to set the stacksize to unlimited prior to run  
 Large pages were not enabled for this run

## Platform Notes

BIOS Configuration : Data Reuse Optimization = Disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp\_rate2006 = 188**

**CPU2006 license:** 9019

**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011

## Base Compiler Invocation

C benchmarks:

  icc -m64

C++ benchmarks:

  icpc -m64

Fortran benchmarks:

  ifort -m64

Benchmarks using both Fortran and C:

  icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
  433.milc: -DSPEC\_CPU\_LP64  
  434.zeusmp: -DSPEC\_CPU\_LP64  
  435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
  437.leslie3d: -DSPEC\_CPU\_LP64  
    444.namd: -DSPEC\_CPU\_LP64  
    447.dealII: -DSPEC\_CPU\_LP64  
    450.soplex: -DSPEC\_CPU\_LP64  
    453.povray: -DSPEC\_CPU\_LP64  
    454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
  465.tonto: -DSPEC\_CPU\_LP64  
  470.lbm: -DSPEC\_CPU\_LP64  
  481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:

  -xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

  -xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp\_rate2006 = 188**

**CPU2006 license:** 9019

**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-ansi-alias -opt-prefetch -static -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp\_rate2006 = 188**

**SPECfp\_rate\_base2006 = 184**

**CPU2006 license:** 9019

**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011

## Peak Optimization Flags (Continued)

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
 -auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
 -B /usr/share/libhugetlbfss/ -Wl,-hugetlbfss-link=BDT

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias  
 -B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
 -inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div  
 -B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto  
 -inline-calloc -opt-malloc-options=3  
 -B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch  
 -static -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C200 M2 (Intel Xeon E5640, 2.67 GHz)

**SPECfp\_rate2006 = 188**

**SPECfp\_rate\_base2006 = 184**

**CPU2006 license:** 9019

**Test date:** Mar-2011

**Test sponsor:** Cisco Systems

**Hardware Availability:** Mar-2011

**Tested by:** Cisco Systems

**Software Availability:** Jan-2011

## Peak Optimization Flags (Continued)

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

<http://www.spec.org/cpu2006/flags/Cisco-BIOS-Platform-Settings.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>

<http://www.spec.org/cpu2006/flags/Cisco-BIOS-Platform-Settings.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 19:22:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 12 April 2011.