



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp®2006 = 27.0

ASUSTek M4A89GTD PRO/USB3 (Phenom II X3 740)

SPECfp_base2006 = 26.3

CPU2006 license: 13


Test date: Jun-2011

Test sponsor: Intel Corporation

Hardware Availability: Feb-2011

Tested by: Intel Corporation

Software Availability: Apr-2011



Hardware

CPU Name: AMD Phenom II X3 740
 CPU Characteristics:
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 3 cores, 1 chip, 3 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Intel Visual Fortran Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1
 (for libraries)
 Auto Parallel: Yes
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 27.0

ASUSTek M4A89GTD PRO/USB3 (Phenom II X3 740)

SPECfp_base2006 = 26.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jun-2011
Hardware Availability: Feb-2011
Software Availability: Apr-2011

L3 Cache: 6 MB I+D on chip per chip
Other Cache: None
Memory: 4 GB (2 x 2 GB 2Rx4 PC3-10600U-9)
Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>278</u>	<u>48.8</u>	279	48.7	278	49.0	<u>278</u>	<u>48.8</u>	279	48.7	278	49.0
416.gamess	<u>964</u>	<u>20.3</u>	964	20.3	963	20.3	859	22.8	<u>859</u>	<u>22.8</u>	859	22.8
433.milc	305	30.1	305	30.1	<u>305</u>	<u>30.1</u>	305	30.1	305	30.1	<u>305</u>	<u>30.1</u>
434.zeusmp	244	37.3	<u>244</u>	<u>37.2</u>	245	37.2	244	37.3	<u>244</u>	<u>37.2</u>	245	37.2
435.gromacs	414	17.3	<u>414</u>	<u>17.3</u>	414	17.3	414	17.3	<u>414</u>	<u>17.3</u>	414	17.3
436.cactusADM	242	49.4	<u>242</u>	<u>49.4</u>	243	49.3	<u>243</u>	<u>49.3</u>	242	49.3	243	49.3
437.leslie3d	<u>360</u>	<u>26.1</u>	360	26.1	360	26.1	<u>360</u>	<u>26.1</u>	360	26.1	360	26.1
444.namd	507	15.8	<u>507</u>	<u>15.8</u>	507	15.8	502	16.0	<u>502</u>	<u>16.0</u>	502	16.0
447.dealII	505	22.6	507	22.6	<u>506</u>	<u>22.6</u>	505	22.6	507	22.6	<u>506</u>	<u>22.6</u>
450.soplex	<u>558</u>	<u>14.9</u>	558	14.9	558	14.9	<u>558</u>	<u>14.9</u>	558	14.9	558	14.9
453.povray	239	22.3	239	22.2	<u>239</u>	<u>22.3</u>	198	26.9	<u>198</u>	<u>26.9</u>	198	26.9
454.calculix	348	23.7	<u>348</u>	<u>23.7</u>	348	23.7	348	23.7	<u>348</u>	<u>23.7</u>	348	23.7
459.GemsFDTD	<u>471</u>	<u>22.5</u>	471	22.5	470	22.6	<u>463</u>	<u>22.9</u>	463	22.9	464	22.9
465.tonto	508	19.4	507	19.4	<u>507</u>	<u>19.4</u>	<u>450</u>	<u>21.9</u>	450	21.9	449	21.9
470.lbm	<u>261</u>	<u>52.6</u>	262	52.5	260	52.8	<u>261</u>	<u>52.6</u>	262	52.5	260	52.8
481.wrf	360	31.0	<u>360</u>	<u>31.1</u>	359	31.1	360	31.0	<u>360</u>	<u>31.1</u>	359	31.1
482.sphinx3	706	27.6	<u>706</u>	<u>27.6</u>	707	27.6	706	27.6	<u>706</u>	<u>27.6</u>	707	27.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

C++ benchmarks:
icl -Qvc9

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 27.0

ASUSTek M4A89GTD PRO/USB3 (Phenom II X3 740)

SPECfp_base2006 = 26.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jun-2011
Hardware Availability: Feb-2011
Software Availability: Apr-2011

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000

C++ benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 -Qprec-div- /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
/F1000000000

Benchmarks using both Fortran and C:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 27.0

ASUSTek M4A89GTD PRO/USB3 (Phenom II X3 740)

SPECfp_base2006 = 26.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jun-2011
Hardware Availability: Feb-2011
Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99
C++ benchmarks:
icl -Qvc9
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
433.milc: basepeak = yes
470.lbm: basepeak = yes
482.sphinx3: basepeak = yes
C++ benchmarks:
444.namd: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
sh1W64M.lib -link /FORCE:MULTIPLE
447.dealII: basepeak = yes
450.soplex: basepeak = yes
453.povray: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE
Fortran benchmarks:
410.bwaves: basepeak = yes
416.gamess: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 27.0

ASUSTek M4A89GTD PRO/USB3 (Phenom II X3 740)

SPECfp_base2006 = 26.3

CPU2006 license: 13

Test date: Jun-2011

Test sponsor: Intel Corporation

Hardware Availability: Feb-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qopt-prefetch -Qparallel
/F1000000000

465.tonto: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qunroll2
-Qauto-ilp32 /F1000000000

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 22:27:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 September 2011.