



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp®2006 = 116

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

SPECfp\_base2006 = 111

CPU2006 license: 3


Test date: Feb-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Dec-2013

Tested by: Hewlett-Packard Company

Software Availability: Sep-2013



### Hardware

CPU Name: Intel Xeon E5-2667 v2  
 CPU Characteristics: Intel Turbo Boost Technology up to 4.00 GHz  
 CPU MHz: 3300  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64) SP3  
 Kernel 3.0.76-0.11-default  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp2006 = **116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

SPECfp\_base2006 = **111**

CPU2006 license: 3

Test date: Feb-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Dec-2013

Tested by: Hewlett-Packard Company

Software Availability: Sep-2013

L3 Cache: 25 MB I+D on chip per chip  
Other Cache: None  
Memory: 128 GB (16 x 8 GB 2Rx4 PC3-14900R-13, ECC)  
Disk Subsystem: 1 x 300 GB 10 K SAS, RAID 0  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>27.2</u>	<u>499</u>	27.2	499	27.6	492	<u>27.2</u>	<u>499</u>	27.2	499	27.6	492
416.gamess	514	38.1	515	38.0	<u>515</u>	<u>38.0</u>	<u>443</u>	<u>44.2</u>	443	44.2	443	44.2
433.milc	<u>112</u>	<u>81.7</u>	113	81.5	112	81.7	<u>112</u>	<u>82.1</u>	112	82.2	112	81.9
434.zeusmp	<u>47.6</u>	<u>191</u>	47.4	192	47.6	191	<u>47.6</u>	<u>191</u>	47.4	192	47.6	191
435.gromacs	<u>141</u>	<u>50.7</u>	141	50.7	141	50.7	<u>141</u>	<u>50.7</u>	141	50.7	141	50.7
436.cactusADM	19.2	621	18.0	663	<u>18.2</u>	<u>655</u>	19.2	621	18.0	663	<u>18.2</u>	<u>655</u>
437.leslie3d	34.0	276	<u>28.2</u>	<u>333</u>	27.8	338	34.0	276	<u>28.2</u>	<u>333</u>	27.8	338
444.namd	288	27.8	<u>288</u>	<u>27.8</u>	289	27.8	<u>283</u>	<u>28.4</u>	283	28.4	283	28.4
447.dealII	169	67.6	<u>169</u>	<u>67.6</u>	169	67.9	169	67.6	<u>169</u>	<u>67.6</u>	169	67.9
450.soplex	<u>153</u>	<u>54.6</u>	153	54.6	152	54.8	<u>153</u>	<u>54.6</u>	153	54.6	152	54.8
453.povray	100	53.1	99.8	53.3	<u>100</u>	<u>53.1</u>	<u>83.2</u>	<u>64.0</u>	83.1	64.0	84.0	63.3
454.calculix	<u>149</u>	<u>55.2</u>	149	55.3	150	55.2	138	59.8	138	59.9	<u>138</u>	<u>59.9</u>
459.GemsFDTD	<u>50.0</u>	<u>212</u>	49.8	213	50.0	212	46.3	229	46.5	228	<u>46.5</u>	<u>228</u>
465.tonto	224	44.0	221	44.5	<u>223</u>	<u>44.2</u>	179	55.1	<u>179</u>	<u>55.0</u>	179	55.0
470.lbm	23.4	587	<u>23.4</u>	<u>587</u>	22.8	602	23.4	587	<u>23.4</u>	<u>587</u>	22.8	602
481.wrf	89.4	125	<u>89.4</u>	<u>125</u>	90.4	124	89.4	125	<u>89.4</u>	<u>125</u>	90.4	124
482.sphinx3	218	89.2	215	90.5	<u>216</u>	<u>90.1</u>	218	89.2	215	90.5	<u>216</u>	<u>90.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Reclaim mode enabled with:
echo 1 > /proc/sys/vm/zone_reclaim_mode
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --localalloc runspec <etc>
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

**SPECfp2006 = 116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

**SPECfp\_base2006 = 111**

**CPU2006 license:** 3  
**Test sponsor:** Hewlett-Packard Company  
**Tested by:** Hewlett-Packard Company

**Test date:** Feb-2014  
**Hardware Availability:** Dec-2013  
**Software Availability:** Sep-2013

### Platform Notes

#### BIOS Configuration:

Intel Hyperthreading Options set to Disabled  
HP Power Profile set to Maximum Performance  
Minimum Processor Idle Power Core State set to C1E state  
Minimum Processor Idle Power Package State set to Package C6 (retention) State  
Memory Power Savings Mode set to Maximum Performance  
Thermal Configuration set to Maximum Cooling  
Collaborative Power Control set to Disabled  
Dynamic Power Capping Functionality set to Disabled  
Processor Power and Utilization Monitoring set to Disabled  
Memory Refresh Rate set to 1x

Sysinfo program /cpu2006/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
running on dl380p-gen8-0sb Sat Feb 1 15:10:55 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2667 v2 @ 3.30GHz
 2 "physical id"s (chips)
 16 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 8
  siblings  : 8
  physical 0: cores 1 2 3 4 8 9 10 11
  physical 1: cores 1 2 3 4 8 9 10 11
cache size : 25600 KB
```

```
From /proc/meminfo
MemTotal:      132130192 kB
HugePages_Total:      0
Hugepagesize:    2048 kB
```

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 11 (x86_64)
```

```
From /etc/*release* /etc/*version*
SuSE-release:
SUSE Linux Enterprise Server 11 (x86_64)
VERSION = 11
PATCHLEVEL = 3
```

```
uname -a:
Linux dl380p-gen8-0sb 3.0.76-0.11-default #1 SMP Fri Jun 14 08:21:43 UTC 2013
(ccab990) x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jan 31 16:19 last=S
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp2006 = 116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

**SPECfp\_base2006 = 111**

**CPU2006 license:** 3

**Test date:** Feb-2014

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Dec-2013

**Tested by:** Hewlett-Packard Company

**Software Availability:** Sep-2013

## Platform Notes (Continued)

SPEC is set to: /cpu2006

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sda2	ext3	274G	13G	260G	5%	/

Additional information from dmidecode:

BIOS HP P70 12/20/2013

Memory:

16x HP 712382-071 8 GB 1866 MHz

8x UNKNOWN NOT AVAILABLE

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 128 GB and the dmidecode description should have one line reading as:

16x HP 712382-071 8 GB 1866 MHz

Regarding the sysinfo display about the CPU cores from /proc/cpuinfo, the correct mapping should display as cores 0 through 7. The mapping should read as the following:

physical 0: cores 0 1 2 3 4 5 6 7

physical 1: cores 0 1 2 3 4 5 6 7

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact"

LD\_LIBRARY\_PATH = "/cpu2006/libs/32:/cpu2006/libs/64:/cpu2006/sh"

OMP\_NUM\_THREADS = "16"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp2006 = 116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

**SPECfp\_base2006 = 111**

**CPU2006 license:** 3

**Test date:** Feb-2014

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Dec-2013

**Tested by:** Hewlett-Packard Company

**Software Availability:** Sep-2013

## Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deall: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

```

C benchmarks:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

C++ benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

```

## Peak Compiler Invocation

```

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp2006 = 116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

**SPECfp\_base2006 = 111**

**CPU2006 license:** 3

**Test date:** Feb-2014

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Dec-2013

**Tested by:** Hewlett-Packard Company

**Software Availability:** Sep-2013

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32  
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp2006 = 116**

ProLiant DL380p Gen8  
(3.30 GHz, Intel Xeon E5-2667 v2)

**SPECfp\_base2006 = 111**

**CPU2006 license:** 3

**Test date:** Feb-2014

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Dec-2013

**Tested by:** Hewlett-Packard Company

**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 22:01:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 11 March 2014.