



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint®2006 = **67.6**

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = **65.2**

CPU2006 license: 13


Test date: May-2014

Test sponsor: Intel Corporation

Hardware Availability: May-2014

Tested by: Intel Corporation

Software Availability: Oct-2013



Hardware

CPU Name: Intel Core i7-4790K
 CPU Characteristics: Intel Turbo Boost Technology up to 4.40 GHz
 CPU MHz: 4000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx4 PC3-12800U-11)
 Disk Subsystem: 180 GB Intel SSD 530
 Other Hardware: None

Software

Operating System: Microsoft Windows 8.1 Pro
 6.3.9600 N/A Build 9600
 Compiler: C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 67.6

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = 65.2

CPU2006 license: 13

Test date: May-2014

Test sponsor: Intel Corporation

Hardware Availability: May-2014

Tested by: Intel Corporation

Software Availability: Oct-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	214	45.7	<u>214</u>	<u>45.6</u>	215	45.5	173	56.6	172	56.9	<u>172</u>	<u>56.9</u>
401.bzip2	297	32.5	<u>297</u>	<u>32.5</u>	297	32.5	296	32.6	296	32.6	<u>296</u>	<u>32.6</u>
403.gcc	208	38.8	207	38.9	<u>207</u>	<u>38.9</u>	194	41.5	194	41.6	<u>194</u>	<u>41.6</u>
429.mcf	<u>104</u>	<u>87.9</u>	104	87.6	103	88.2	<u>104</u>	<u>87.9</u>	104	87.6	103	88.2
445.gobmk	297	35.3	<u>297</u>	<u>35.3</u>	298	35.2	281	37.3	280	37.5	<u>280</u>	<u>37.4</u>
456.hammer	107	87.0	<u>107</u>	<u>87.0</u>	107	87.0	107	87.0	<u>107</u>	<u>87.0</u>	107	87.0
458.sjeng	303	40.0	<u>303</u>	<u>39.9</u>	303	39.9	303	40.0	<u>303</u>	<u>39.9</u>	303	39.9
462.libquantum	<u>13.5</u>	<u>1530</u>	13.0	1590	13.6	1520	<u>13.5</u>	<u>1530</u>	13.0	1590	13.6	1520
464.h264ref	291	76.2	287	77.1	<u>288</u>	<u>76.9</u>	291	76.2	287	77.1	<u>288</u>	<u>76.9</u>
471.omnetpp	<u>216</u>	<u>28.9</u>	216	29.0	221	28.3	202	30.9	198	31.6	<u>202</u>	<u>31.0</u>
473.astar	180	39.1	<u>180</u>	<u>39.0</u>	181	38.9	180	39.1	<u>180</u>	<u>39.0</u>	181	38.9
483.xalancbmk	95.5	72.3	96.0	71.9	<u>95.7</u>	<u>72.1</u>	95.5	72.3	96.0	71.9	<u>95.7</u>	<u>72.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 14.0 was set up to generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Platform Notes

Sysinfo program C:\SPEC14.0\Docs\sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 # \$ \8787f7622badcf24e01c368b1db4377c
running on Z97A Mon May 19 15:26:55 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 8.1 Pro
OS Version    : 6.3.9600 N/A Build 9600
System Manufacturer: ASUS
System Model   : All Series
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~4001 Mhz
BIOS Version  : American Megatrends Inc. 0702, 4/23/2014
Total Physical Memory: 8,069 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 67.6

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = 65.2

CPU2006 license: 13

Test date: May-2014

Test sponsor: Intel Corporation

Hardware Availability: May-2014

Tested by: Intel Corporation

Software Availability: Oct-2013

Platform Notes (Continued)

L2CacheSize : 1024
L3CacheSize : 8192
MaxClockSpeed : 4001
Name : Intel(R) Core(TM) i7-4790K CPU @ 4.00GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)

BIOS: SATA mode set to RAID

Windows Disk Driver: Intel Rapid Storage Technology 12.9.0.1001

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
-DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 67.6

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = 65.2

CPU2006 license: 13

Test date: May-2014

Test sponsor: Intel Corporation

Hardware Availability: May-2014

Tested by: Intel Corporation

Software Availability: Oct-2013

Base Portability Flags (Continued)

483.xalanbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F512000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F512000000 shlw64M.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 67.6

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = 65.2

CPU2006 license: 13

Test date: May-2014

Test sponsor: Intel Corporation

Hardware Availability: May-2014

Tested by: Intel Corporation

Software Availability: Oct-2013

Peak Optimization Flags (Continued)

401.bzip2: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
-Qauto-ilp32 /F512000000

403.gcc: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 67.6

ASUS Z97-A motherboard (Intel Core i7-4790K)

SPECint_base2006 = 65.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: May-2014

Hardware Availability: May-2014

Software Availability: Oct-2013

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 9 10:44:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 18 June 2014.