



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp<sup>®</sup>\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13


Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013



### Hardware

CPU Name: Intel Core i5-3340  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz  
 CPU MHz: 3100  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601  
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;  
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1  
 Auto Parallel: No

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13

Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

L3 Cache: 6 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)  
 Disk Subsystem: 250 GB Seagate SATA HDD, 7200 RPM  
 Other Hardware: None

File System: NTFS  
 System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	614	88.4	<b>597</b>	<b>91.2</b>	595	91.2	4	614	88.4	<b>597</b>	<b>91.2</b>	595	91.2
416.gamess	4	620	126	620	126	<b>620</b>	<b>126</b>	4	620	126	620	126	<b>620</b>	<b>126</b>
433.milc	4	371	98.8	<b>371</b>	<b>98.8</b>	372	98.8	4	371	98.8	<b>371</b>	<b>98.8</b>	372	98.8
434.zeusmp	4	<b>292</b>	<b>124</b>	293	124	287	127	4	<b>292</b>	<b>124</b>	293	124	287	127
435.gromacs	4	216	132	<b>216</b>	<b>132</b>	217	132	4	216	132	<b>216</b>	<b>132</b>	217	132
436.cactusADM	4	362	132	359	133	<b>361</b>	<b>132</b>	4	362	132	359	133	<b>361</b>	<b>132</b>
437.leslie3d	4	<b>643</b>	<b>58.4</b>	643	58.4	644	58.4	4	<b>643</b>	<b>58.4</b>	643	58.4	644	58.4
444.namd	4	371	86.4	<b>371</b>	<b>86.4</b>	374	85.6	4	370	86.8	<b>370</b>	<b>86.8</b>	371	86.4
447.dealII	4	278	165	259	177	<b>270</b>	<b>169</b>	4	278	165	259	177	<b>270</b>	<b>169</b>
450.soplex	4	520	64.4	518	64.4	<b>519</b>	<b>64.4</b>	4	505	66.0	506	66.0	<b>505</b>	<b>66.0</b>
453.povray	4	<b>135</b>	<b>158</b>	135	158	135	158	4	<b>111</b>	<b>191</b>	111	192	111	191
454.calculix	4	227	146	226	146	<b>227</b>	<b>146</b>	4	227	146	226	146	<b>227</b>	<b>146</b>
459.GemsFDTD	4	822	51.6	<b>822</b>	<b>51.6</b>	823	51.6	4	822	51.6	<b>822</b>	<b>51.6</b>	823	51.6
465.tonto	4	350	112	358	110	<b>352</b>	<b>112</b>	4	320	123	319	124	<b>320</b>	<b>123</b>
470.lbm	4	<b>507</b>	<b>108</b>	506	109	507	108	4	<b>507</b>	<b>108</b>	506	109	507	108
481.wrf	4	402	111	<b>402</b>	<b>111</b>	403	111	4	402	111	<b>402</b>	<b>111</b>	403	111
482.sphinx3	4	711	110	<b>712</b>	<b>110</b>	712	110	4	711	110	<b>712</b>	<b>110</b>	712	110

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:  
 "ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

## Submit Notes

Processes were bound to specific processors using the start command with the /affinity switch. The config file option 'submit' was used to generate the affinity mask for each process.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13

Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

## Platform Notes

Sysinfo program C:\SPEC13.1/Docs/sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 # \$ \8787f7622badcf24e01c368b1db4377c  
running on Clt7054D218890C Sun Jan 19 04:18:22 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

OS Name : Microsoft Windows 7 Enterprise  
OS Version : 6.1.7601 Service Pack 1 Build 7601  
System Manufacturer: INTEL\_  
System Model : DQ77MK\_\_  
Processor(s) : 1 Processor(s) Installed.  
 [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3101 Mhz  
BIOS Version : Intel Corp. MKQ7710H.86A.0054.2012.1120.1444, 11/20/2012  
Total Physical Memory: 3,912 MB

Trying 'wmic cpu get /value'

DeviceID : CPU0  
L2CacheSize : 1024  
L3CacheSize : 6144  
MaxClockSpeed : 3101  
Name : Intel(R) Core(TM) i5-3340 CPU @ 3.10GHz  
NumberOfCores : 4  
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

BIOS: SATA mode set to RAID  
Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066  
Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply  
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

## General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:  
icl -Qvc10 -Qstd=c99

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13

Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

## Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc10

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 /names:lowercase /assume:underscore  
 437.leslie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 -Qoption,cpp,--ms\_incompat\_treatment\_of\_commas\_in\_macros  
 450.soplex: -DSPEC\_CPU\_P64  
 453.povray: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NEED\_INVHYP -DNEED\_INVHYP  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER /names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F1000000000 -link /FORCE:MULTIPLE

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13

Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 107

Intel DQ77MK motherboard (Intel Core i5-3340)

SPECfp\_rate\_base2006 = 105

CPU2006 license: 13

Test date: Jan-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

## Peak Optimization Flags (Continued)

```
453.povray: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
            -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32 /F1000000000
            sh1W64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
            -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
            -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Sep 9 10:56:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 July 2014.