



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp®2006 = 120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 = 112

CPU2006 license: 9050


Test date: Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability: Mar-2016

Tested by: Quanta Computer Inc.

Software Availability: Mar-2016



SPECfp_base2006 = 112

SPECfp2006 = 120

Hardware

CPU Name: Intel Xeon E7-8890 v3
CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz
CPU MHz: 2500
FPU: Integrated
CPU(s) enabled: 72 cores, 4 chips, 18 cores/chip, 2 threads/core
CPU(s) orderable: 1,2,3,4 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 7.1 (Maipo)
Compiler: 3.10.0-229.el7.x86_64
C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux;
Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux
Auto Parallel: Yes
File System: xfs

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 = 112

CPU2006 license: 9050

Test date: Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability: Mar-2016

Tested by: Quanta Computer Inc.

Software Availability: Mar-2016

L3 Cache:	45 MB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (32 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)
Disk Subsystem:	1 x 480 GB SSD
Other Hardware:	None

System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	10.6	1280	10.4	1310	<u>10.4</u>	<u>1310</u>	10.6	1280	10.4	1310	<u>10.4</u>	<u>1310</u>
416.gamess	<u>593</u>	<u>33.0</u>	591	33.1	593	33.0	<u>483</u>	<u>40.6</u>	481	40.7	<u>481</u>	<u>40.7</u>
433.milc	141	65.0	<u>141</u>	<u>65.1</u>	140	65.4	<u>141</u>	<u>65.0</u>	<u>141</u>	<u>65.1</u>	140	65.4
434.zeusmp	54.6	167	<u>54.3</u>	<u>168</u>	53.9	169	<u>54.6</u>	<u>167</u>	<u>54.3</u>	<u>168</u>	53.9	169
435.gromacs	190	37.6	<u>191</u>	<u>37.4</u>	193	37.0	<u>190</u>	<u>37.6</u>	<u>191</u>	<u>37.4</u>	193	37.0
436.cactusADM	10.8	1100	11.5	1040	<u>11.2</u>	<u>1070</u>	10.8	1100	11.5	1040	<u>11.2</u>	<u>1070</u>
437.leslie3d	36.6	257	<u>36.1</u>	<u>261</u>	35.6	264	<u>36.6</u>	<u>257</u>	<u>36.1</u>	<u>261</u>	35.6	264
444.namd	<u>289</u>	<u>27.8</u>	288	27.8	289	27.8	<u>280</u>	<u>28.6</u>	280	28.6	280	28.6
447.dealII	202	56.7	<u>202</u>	<u>56.7</u>	202	56.7	<u>202</u>	<u>56.7</u>	<u>202</u>	<u>56.7</u>	202	56.7
450.soplex	197	42.2	196	42.5	<u>197</u>	<u>42.4</u>	197	42.2	196	42.5	<u>197</u>	<u>42.4</u>
453.povray	<u>97.2</u>	<u>54.7</u>	96.2	55.3	98.7	53.9	86.7	61.4	86.9	61.2	<u>86.8</u>	<u>61.3</u>
454.calculix	174	47.5	<u>174</u>	<u>47.4</u>	174	47.4	<u>152</u>	<u>54.3</u>	156	53.0	152	54.4
459.GemsFDTD	<u>54.9</u>	<u>193</u>	56.1	189	50.2	212	<u>40.2</u>	<u>264</u>	41.6	255	39.5	268
465.tonto	284	34.7	267	36.9	<u>268</u>	<u>36.7</u>	197	50.0	200	49.3	<u>197</u>	<u>50.0</u>
470.lbm	8.57	1600	7.73	1780	<u>7.99</u>	<u>1720</u>	8.57	1600	7.73	1780	<u>7.99</u>	<u>1720</u>
481.wrf	104	107	<u>104</u>	<u>107</u>	103	109	104	107	<u>104</u>	<u>107</u>	103	109
482.sphinx3	302	64.5	<u>303</u>	<u>64.3</u>	303	64.3	<u>302</u>	<u>64.5</u>	<u>303</u>	<u>64.3</u>	303	64.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

```
Sysinfo program /home/speccpu-auto-install/config/sysinfo.rev6914
$Rev: 6914 $ $Date::: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Sun Mar 13 10:12:16 2016
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 =

120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 =

112

CPU2006 license: 9050

Test date:

Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability:

Mar-2016

Tested by: Quanta Computer Inc.

Software Availability:

Mar-2016

Platform Notes (Continued)

```
model name : Intel(R) Xeon(R) CPU E7-8890 v3 @ 2.50GHz
        4 "physical id"s (chips)
        144 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 18
siblings : 36
physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 2: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 3: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
cache size : 46080 KB
```

```
From /proc/meminfo
MemTotal:      528058100 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
From /etc/*release* /etc/*version*
os-release:
  NAME="Red Hat Enterprise Linux Server"
  VERSION="7.1 (Maipo)"
  ID="rhel"
  ID_LIKE="fedora"
  VERSION_ID="7.1"
  PRETTY_NAME="Red Hat Enterprise Linux Server 7.1 (Maipo)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:redhat:enterprise_linux:7.1:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.1:ga:server
```

```
uname -a:
Linux localhost.localdomain 3.10.0-229.el7.x86_64 #1 SMP Thu Jan 29 18:37:38
EST 2015 x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Mar 11 15:41 last=5
```

```
SPEC is set to: /home/speccpu-auto-install
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda5        xfs   393G  7.9G  385G   2% /home
Additional information from dmidecode:
```

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS American Megatrends Inc. S4L_3B08 10/15/2015

Memory:

32x Micron 36ASF2G72PZ-2G1A2 16 GB 2 rank 2133 MHz, configured at 1600 MHz

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 =

120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 =

112

CPU2006 license: 9050

Test date: Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability: Mar-2016

Tested by: Quanta Computer Inc.

Software Availability: Mar-2016

Platform Notes (Continued)

64x NO DIMM NO DIMM

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact,1,0"

LD_LIBRARY_PATH = "/home/speccpu-auto-install/libs/32:/home/speccpu-auto-install/libs/64:/home/speccpu-auto-install/sh"

OMP_NUM_THREADS = "72"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7.1

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent_hugepage/enabled

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 = 112

CPU2006 license: 9050

Test date: Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability: Mar-2016

Tested by: Quanta Computer Inc.

Software Availability: Mar-2016

Base Portability Flags (Continued)

470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 =

120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 =

112

CPU2006 license: 9050

Test date:

Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability:

Mar-2016

Tested by: Quanta Computer Inc.

Software Availability:

Mar-2016

Peak Optimization Flags (Continued)

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

```
444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
           -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
           -par-num-threads=1(pass 1) -prof-use(pass 2) -fno-alias
           -auto-ilp32
```

447.dealII: basepeak = yes

450.soplex: basepeak = yes

```
453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
             -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
             -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll14
             -ansi-alias
```

Fortran benchmarks:

410.bwaves: basepeak = yes

```
416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
             -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
             -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12
             -inline-level=0 -scalar-rep-
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

```
459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
                -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
                -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12
                -inline-level=0 -opt-prefetch -parallel
```

```
465.tonto: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
            -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
            -par-num-threads=1(pass 1) -prof-use(pass 2) -inline-calloc
            -opt-malloc-options=3 -auto -unroll14
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 120

QuantaGrid Q71L-4U (Intel Xeon E7-8890 v3)

SPECfp_base2006 = 112

CPU2006 license: 9050

Test date: Mar-2016

Test sponsor: Quanta Computer Inc.

Hardware Availability: Mar-2016

Tested by: Quanta Computer Inc.

Software Availability: Mar-2016

Peak Optimization Flags (Continued)

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Quanta-Computer-Inc-Platform-Settings-V1.0.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Quanta-Computer-Inc-Platform-Settings-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Apr 5 14:55:32 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 5 April 2016.