



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28


Test Date: Aug-2024

Test Sponsor: Lenovo Global Technology

Hardware Availability: Oct-2023

Tested by: Lenovo Global Technology

Software Availability: Jun-2024



Results Table

Benchmark	Base										Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	OMP	32	30	307	5.05	307	5.05	308	5.03	OMP	32	30	307	5.05	307	5.05	308	5.03
613.soma_s	OMP	32	30	245	6.54	239	6.70	246	6.51	OMP	32	30	245	6.54	239	6.70	246	6.51
618.tealeaf_s	OMP	32	30	1186	1.73	1218	1.68	1185	1.73	OMP	32	30	1186	1.73	1218	1.68	1185	1.73
619.clvleaf_s	OMP	32	30	963	1.71	962	1.72	962	1.72	OMP	32	30	963	1.71	962	1.72	962	1.72
621.miniswp_s	OMP	32	30	155	7.10	155	7.09	155	7.10	OMP	32	30	155	7.10	155	7.09	155	7.10
628.pot3d_s	OMP	32	30	1027	1.63	1034	1.62	1031	1.63	OMP	32	30	1027	1.63	1034	1.62	1031	1.63
632.sph_exa_s	OMP	32	30	285	8.08	286	8.04	286	8.05	OMP	32	30	285	8.08	286	8.04	286	8.05
634.hpgmgfv_s	OMP	32	30	504	1.93	505	1.93	505	1.93	OMP	32	30	504	1.93	505	1.93	505	1.93
635.weather_s	OMP	32	30	545	4.77	544	4.78	548	4.74	OMP	32	30	545	4.77	544	4.78	548	4.74

SPEChpc 2021_sml_base = 3.52

SPEChpc 2021_sml_peak = 3.52

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2024
Hardware Availability: Oct-2023
Software Availability: Jun-2024

Hardware Summary

Type of System: Homogenous
Compute Node: ThinkSystem SR950V3
Interconnect: N/A
Compute Nodes Used: 1
Total Chips: 8
Total Cores: 480
Total Threads: 480
Total Memory: 4 TB
Max. Peak Threads: 30

Software Summary

Compiler: Intel oneAPI 2024 Update 2
Build 20240602
MPI Library: Intel MPI Library for Linux* OS
Version 2021 Update 13 Build 20240515
Other MPI Info: --
Other Software: --
Base Parallel Model: OMP
Base Ranks Run: 32
Base Threads Run: 30
Peak Parallel Models: OMP
Minimum Peak Ranks: 32
Maximum Peak Ranks: 32
Max. Peak Threads: 30
Min. Peak Threads: 30

Node Description: ThinkSystem SR950V3

Hardware

Number of nodes: 1
Uses of the node: compute
Vendor: Lenovo Global Technology
Model: ThinkSystem SR950V3
CPU Name: Intel Xeon 8490H
CPU(s) orderable: 8 chips
Chips enabled: 8
Cores enabled: 480
Cores per chip: 60
Threads per core: 1
CPU Characteristics: Intel Turbo Boost Technology up to 3.5 GHz
CPU MHz: 1900
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 115200 KB I+D on chip per chip
Other Cache: None
Memory: 4 TB (64 x 64 GB 2Rx4 PC4-4800V)
Disk Subsystem: 1 x 960 GB M.2 NVME SSD
Other Hardware: None
Accel Count: 0
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: None
Number of Adapters: 0
Slot Type: None
Data Rate: None

Software

Accelerator Driver: --
Adapter: None
Adapter Driver: None
Adapter Firmware: None
Operating System: Red Hat Enterprise Linux Server release 9,
Kernel 5.14.0-70.22.1.el9.x86_64
Local File System: xfs
Shared File System: None
System State: Multi-user, run level 3
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2024
Hardware Availability: Oct-2023
Software Availability: Jun-2024

Node Description: ThinkSystem SR950V3

Hardware (Continued)

Ports Used: 0
Interconnect Type: None

Interconnect Description: N/A

Hardware

Vendor: N/A
Model: N/A
Switch Model: N/A
Number of Switches: 0
Number of Ports: 0
Data Rate: N/A
Firmware: N/A
Topology: N/A
Primary Use: N/A

Software

: --

Submit Notes

The config file option 'submit' was used.

Compiler Version Notes

=====
FC 619.clvleaf_s(base) 628.pot3d_s(base) 635.weather_s(base)

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
2024.2.0 Build 20240602
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
ifx: command line warning #10006: ignoring unknown option '-std=c++14'
ifx: command line warning #10157: ignoring option '-W'; argument is of wrong
type
ifx: command line error: no files specified; for help type "ifx -help"

=====
CXXC 632.sph_exa_s(base)

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2024.2.0 Build 20240602
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
icpx: warning: -Z-reserved-lib-stdc++: 'linker' input unused
[-Wunused-command-line-argument]

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2024
Hardware Availability: Oct-2023
Software Availability: Jun-2024

Compiler Version Notes (Continued)

=====
CC 605.lbm_s(base) 613.soma_s(base) 618.tealeaf_s(base) 621.miniswp_s(base)
634.hpgmgfv_s(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
Version 2024.2.0 Build 20240602
Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
icx: warning: -Z-reserved-lib-stdc++: 'linker' input unused
[-Wunused-command-line-argument]

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpiicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx

Base Portability Flags

605.lbm_s: -lstdc++ -std=c++14
613.soma_s: -lstdc++ -std=c++14 -DSPEC_NO_VAR_ARRAY_REDUCE
618.tealeaf_s: -lstdc++ -std=c++14
619.clvleaf_s: -lstdc++ -std=c++14
621.miniswp_s: -lstdc++ -std=c++14
628.pot3d_s: -lstdc++ -std=c++14
632.sph_exa_s: -lstdc++ -std=c++14
634.hpgmgfv_s: -lstdc++ -std=c++14
635.weather_s: -lstdc++ -std=c++14

Base Optimization Flags

C benchmarks:
-Ofast -xCORE-AVX512 -ipo -fiopenmp -ansi-alias

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2024
Hardware Availability: Oct-2023
Software Availability: Jun-2024

Base Optimization Flags (Continued)

C++ benchmarks:

-Ofast -xCORE-AVX512 -ipo -fiopenmp -ansi-alias

Fortran benchmarks:

-Ofast -xCORE-AVX512 -ipo -fiopenmp -nostandard-realloc-lhs
-align array64byte

Base Other Flags

C benchmarks (except as noted below):

-Wno-incompatible-function-pointer-types

613.soma_s: -Wno-incompatible-function-pointer-types

C++ benchmarks:

-Wno-incompatible-function-pointer-types

Fortran benchmarks:

-Wno-incompatible-function-pointer-types

Peak Optimization Flags

C benchmarks:

605.lbm_s: basepeak = yes

613.soma_s: basepeak = yes

618.tealeaf_s: basepeak = yes

621.miniswp_s: basepeak = yes

634.hpgmgfv_s: basepeak = yes

C++ benchmarks:

632.sph_exa_s: basepeak = yes

Fortran benchmarks:

619.cvlleaf_s: basepeak = yes

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPEChpc 2021_sml_base = 3.52

ThinkSystem SR950V3 (Intel Xeon 8490H)

SPEChpc 2021_sml_peak = 3.52

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2024
Hardware Availability: Oct-2023
Software Availability: Jun-2024

Peak Optimization Flags (Continued)

628.pot3d_s: basepeak = yes

635.weather_s: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-11-13.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-11-13.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.8 on 2024-08-07 23:38:17-0400.
Report generated on 2024-11-13 14:38:08 by hpc2021 PDF formatter v1.0.3.
Originally published on 2024-11-13.