



SPEC[®] MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM_peak2007 = Not Run

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiM_base2007 = 74.0

MPI2007 license: 28


Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020



Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
104.milc	768	13.9	112	13.8	113	<u>13.9</u>	<u>113</u>									
107.leslie3d	768	<u>60.2</u>	<u>86.6</u>	60.0	87.0	60.8	85.9									
113.GemsFDTD	768	221	28.6	216	29.3	<u>217</u>	<u>29.1</u>									
115.fds4	768	27.0	72.3	27.3	71.5	<u>27.3</u>	<u>71.5</u>									
121.pop2	768	<u>100</u>	<u>41.1</u>	100	41.1	100	41.3									
122.tachyon	768	22.1	126	<u>22.1</u>	<u>126</u>	22.5	124									
126.lammps	768	<u>101</u>	<u>28.9</u>	101	28.9	101	28.9									
127.wrf2	768	48.3	161	49.6	157	<u>48.9</u>	<u>159</u>									
128.GAPgeofem	768	20.2	102	<u>20.5</u>	<u>101</u>	20.6	100									
129.tera_tf	768	32.3	85.7	34.0	81.5	<u>34.0</u>	<u>81.5</u>									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM_peak2007 = Not Run

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiM_base2007 = 74.0

MPI2007 license: 28

Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	768	64.5	59.2	64.7	59.0	63.2	60.4							
132.zeusmp2	768	43.5	71.4	43.2	71.8	43.7	71.0							
137.lu	768	30.8	119	31.1	118	31.0	119							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogeneous
 Compute Node: ThinkSystem SR665
 Interconnect: Mellanox ConnectX-6 HDR
 File Server Node: NFS
 Total Compute Nodes: 6
 Total Chips: 12
 Total Cores: 768
 Total Threads: 768
 Total Memory: 6 TB
 Base Ranks Run: 768
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

C Compiler: AMD Optimizing C Compiler for Linux
 Version 2.1 Build 1030.2019_11_12
 C++ Compiler: AMD Optimizing C++ Compiler for Linux
 Version 2.1 Build 1030.2019_11_12
 Fortran Compiler: AMD Optimizing Fortran Compiler for Linux
 Version 2.1 Build 1030.2019_11_12
 Base Pointers: 64-bit
 Peak Pointers: Not Applicable
 MPI Library: OpenMPI MPI Library
 Version 4.0.2
 Other MPI Info: None
 Pre-processors: No
 Other Software: None

Node Description: ThinkSystem SR665

Hardware

Number of nodes: 6
 Uses of the node: compute
 Vendor: Lenovo Global Technology
 Model: SR665
 CPU Name: AMD EPYC 7H12
 CPU(s) orderable: 1-2 chips
 Chips enabled: 2
 Cores enabled: 128
 Cores per chip: 64
 Threads per core: 1
 CPU Characteristics: None
 CPU MHz: 2600
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 256 MB I+D on chip per chip
 16 MB shared / 4 cores
 Other Cache: None
 Memory: 1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)
 Disk Subsystem: 1 x 480 GB SATA 2.5" SSD
 Other Hardware: None
 Adapter: Mellanox ConnectX-6 HDR Infiniband
 Number of Adapters: 1
 Slot Type: PCI-Express 4.0 x16

Software

Adapter: Mellanox ConnectX-6 HDR Infiniband
 Adapter Driver: 4.7-1.0.0.1.2
 Adapter Firmware: 20.25.2006
 Operating System: Red Hat Enterprise Linux Server release 8.1,
 4.18.0-147.el8.x86_64
 Local File System: xfs
 Shared File System: None
 System State: Multi-user, run level 3
 Other Software: None

Continued on next page



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM_peak2007 = Not Run

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiM_base2007 = 74.0

MPI2007 license: 28

Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020

Node Description: ThinkSystem SR665

Data Rate:	200 Gbs/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband Adapter

Node Description: NFS

Hardware	
Number of nodes:	1
Uses of the node:	Fileserver
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR665
CPU Name:	AMD EPYC 7H12 CPU
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	128
Cores per chip:	64
Threads per core:	1
CPU Characteristics:	None
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip
	16 MB shared / 4 cores
Other Cache:	None
Memory:	1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)
Disk Subsystem:	1 x 480 GB SATA 2.5" SSD
Other Hardware:	None
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gb/s
Ports Used:	1
Interconnect Type:	Mellanox ConnectX-6 HDR Infiniband

Software	
Adapter:	Mellanox ConnectX-6 HDR Infiniband
Adapter Driver:	4.7-1.0.0.1.2
Adapter Firmware:	20.25.2006
Operating System:	Red Hat Enterprise Linux Server release 8.1
Local File System:	None
Shared File System:	NFS
System State:	Multi-User, run level 3
Other Software:	None

Interconnect Description: Mellanox ConnectX-6 HDR

Hardware	
Vendor:	Mellanox
Model:	Infiniband EDR 100Gb/s Switch
Switch Model:	SB7800 Series
Number of Switches:	1
Number of Ports:	36
Data Rate:	100 Gb/s
Firmware:	3.9.0300
Topology:	Mesh

Software

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM_peak2007 = Not Run

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiM_base2007 = 74.0

MPI2007 license: 28

Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020

Interconnect Description: Mellanox ConnectX-6 HDR

Primary Use: MPI Traffic

Submit Notes

The config file option 'submit' was used.

General Notes

MPI startup command:

mpiexec command was used to start MPI jobs.

RAM configuration:

Compute nodes have 1 x 32 GB RDIMM on each memory channel.

Add "idle=poll" into grub

BIOS settings:

Operating Mode : Maximum Performance Mode

Hyper-Threading Technology (SMT): Enabled

NPS4

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Base Compiler Invocation

C benchmarks:

/opt/openmpi/0402_A21_H47_RH81/bin/mpicc

C++ benchmarks:

126.lammps: /opt/openmpi/0402_A21_H47_RH81/bin/mpicxx

Fortran benchmarks:

/opt/openmpi/0402_A21_H47_RH81/bin/mp ifort

Benchmarks using both Fortran and C:

/opt/openmpi/0402_A21_H47_RH81/bin/mpicc

/opt/openmpi/0402_A21_H47_RH81/bin/mp ifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 4



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM_peak2007 = Not Run

ThinkSystem SR665
(AMD EPYC 7H12, 2.6 GHz)

SPECmpiM_base2007 = 74.0

MPI2007 license: 28

Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020

Base Portability Flags (Continued)

126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX -Wno-return-type

Base Optimization Flags

C benchmarks:

-Ofast -flto -ffast-math -march=znver2 -mavx2
-L/home/AMD_libm/amd-libm/lib -lamdlibm

C++ benchmarks:

126.lammps: -Ofast -flto -ffast-math -march=znver2 -mavx2
-L/home/AMD_libm/amd-libm/lib -lamdlibm

Fortran benchmarks:

-Ofast -flto -ffast-math -march=znver2 -funroll-loops -mavx2
-L/home/AMD_libm/amd-libm/lib -lamdlibm

Benchmarks using both Fortran and C:

-Ofast -flto -ffast-math -march=znver2 -mavx2 -funroll-loops
-L/home/AMD_libm/amd-libm/lib -lamdlibm

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Wed May 6 11:57:29 2020 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 6 May 2020.