



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 575 (1900 MHz, 16 CPU)

SPECompMpeak2001 = 56211
SPECompMbase2001 = 45275

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Dec-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	85.1	70503	75.5	79419	
312.swim_m	6000	106	56455	79.3	75664	
314.mgrid_m	7300	217	33623	109	66679	
316.applu_m	4000	53.7	74435	46.3	86343	
318.galgel_m	5100	124	40964	112	45489	
320.earthquake_m	2600	150	17292	82.2	31618	
324.apsi_m	3400	76.5	44473	70.1	48515	
326.gafort_m	8700	149	58552	135	64526	
328.fma3d_m	4600	179	25666	166	27701	
330.art_m	6400	56.1	114037	48.4	132307	
332.ammp_m	7000	230	30468	226	31012	

Hardware

CPU: POWER5+
 CPU MHz: 1900
 FPU: Integrated
 CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip (SMT on)
 CPU(s) orderable: 8,16
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified, shared (on chip)/chip
 L3 Cache: 36MB unified (off-chip)/DCM, 8 DCMs/SUT
 Other Cache: None
 Memory: 64x2GB
 Disk Subsystem: 2x73GB SCSI, 15K RPM
 Other Hardware: None

Software

OpenMP Threads: 32
 Parallel: OpenMP
 Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 XL Fortran Enterprise Edition Version 10.1 for AIX
 Other Software: ESSL 4.2.0.2
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags & Environment Variables

-qfixed used in: 310.wupwise_m, 312.swim_m, 314.mgrid_m, 316.applu_m, 324.apsi_m
 -qfixed=80 used in: 318.galgel_m
 -qsuffix=f=f90 used in: 318.galgel_m, 326.gafort_m, 328.fma3d_m

Base Flags

C: -qpdf1/pdf2
 -q64 -q05 -blpdata -qalign=natural -qhot=arraypad -Q -qsmp=omp
 FORTRAN: -O5 -qipa=noobject -qipa=partition=large -qmaxmem=-1 -qsmp=omp

Base & Peak User Environment:

OMP_NUM_THREADS=32
 OMP_DYNAMIC=FALSE
 XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=1
 MALLOCMULTIHEAP=1

Peak Flags:

-qsmp=omp used in all cases
 310.wupwise_m: -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -q64 -btextpsize:64K -bdatapsize:64K
 312.swim_m: -O5 -qarch=pwr3 -qtune=pwr3 -q64 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K
 314.mgrid_m: -O5 -qipa=partition=large -qalign=struct=natural -q64 -btextpsize:64K -bdatapsize:64K
 316.applu_m: -O3 -qarch=pwr4 -qtune=pwr4 -q64 -btextpsize:64K -bdatapsize:64K
 318.galgel_m: -O5 -qarch=pwr3 -qtune=pwr3 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -lmass -qessl -lesslsm



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 575 (1900 MHz, 16 CPU)

SPECompMpeak2001 = 56211

SPECompMbase2001 = 45275

SPEC license #HPG0005 Tested by: IBM Test site: Austin, TX Test date: Dec-2005 Hardware AvailFeb-2006 Software AvailFeb-2006

Notes/Tuning Information (Continued)

```

EXTRA_LDFLAGS=-bmaxdata:0x80000000
320.quake_m: -qpdf1/pdf2
              -O5 -qfdpr -q64 -bdatapsize:64K
              fdpr -q -O3
325.apsi_m:  -O5 -qalign=struct=natural -bdatapsize:64K -bstacksize:64K
              EXTRA_LDFLAGS=-bmaxdata:0x80000000
              XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
              OMP_NUM_THREADS=16
326.gafort_m: -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -qalign=struct=natural
              -btextpsize:64K -bdatapsize:64K -bstacksize:64K -lhm -lmass -qessl -lesslmp
              EXTRA_LDFLAGS=-bmaxdata:0x80000000
328.fma3d_m:  -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -btextpsize:64K -bdatapsize:64K
              -bstacksize:64K -lmass -qessl -lesslmp
              EXTRA_LDFLAGS=-bmaxdata:0x80000000
330.art_m:    -qpdf1/pdf2
              -O5 -qfdpr -q64 -btextpsize:64K -bdatapsize:64K -lesslmp
              fdpr -q -O3
              EXTRA_CFLAGS= -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16
332.amp_m:   -qpdf1/pdf2
              -O5 -qipa=partition=large -qmaxmem=-1 -q64 -btextpsize:64K -bdatapsize:64K

```

Alternate sources:

Add critical region around update of linked list in parallel loop.
 Approved src.alt available as ompm-purduel-20040324.tar.gz
 Used for 330.art_m, base and peak.

Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used
 with 312.swim_m, 316.applu_m, 320.quake_m, 326.gafort_m.

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

ESSL: Engineering and Scientific Subroutine Library

ANSI C89: IBM XL C for AIX invoked as xlc_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf_r

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=1600 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${\ $ \$SPECUSERNUM; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.