



# SPEC® OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = NC

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = NC

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

- Threads
- 350.md
- 351.bwaves
- 352.nab
- 357.bt331
- 358.botsalgn
- 359.botsspar
- 360.ilbdc
- 362.fma3d
- 363.swim
- 367.imagick
- 370.mgrid331
- 371.applu331
- 372
- 376.kd\_tree

### Hardware

CPU Name: Intel Xeon Platinum 8180  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.80 GHz  
 CPU MHz: 2500  
 CPU MHz Maximum: 3800  
 FPU: Integrated

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server 7.3 (Maipo)  
 Linux Kernel 3.10.0-514.el7.x86\_64

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

## Huawei

SPECompG\_peak2012 = **NC**

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = **NC**

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

CPU(s) enabled: 112 cores, 4 chips, 28 cores/chip, 2 threads/core  
 CPU(s) orderable: 2, 4 Chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 38.5 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 768 GB (24 x 32 GB 2Rx4 PC4-2666V, running at 2666 MHz)  
 Disk Subsystem: 2 x 600 GB 10K RPM SAS  
 Other Hardware: None  
 Base Threads Run: 224  
 Minimum Peak Threads: 112  
 Maximum Peak Threads: 224

Compiler: C/C++/Fortran: Version 17.0.4.196 of Intel Parallel Studio XE 2017 for Linux;  
 Auto Parallel: No  
 System: xfs  
 System State: run-level 3  
 Base Pointers: 64-bit  
 Link Pointers: 64-bit  
 Other Software: None

## Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
351.bwaves	224	NC	NC	NC	NC	NC	NC	112	NC	NC	NC	NC	NC	NC
352.nab	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
357.bt331	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
358.botsalgn	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
359.botsspar	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
360.ilbdc	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
362.fma3d	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
363.sw	112	NC	NC	NC	NC	NC	NC	112	NC	NC	NC	NC	NC	NC
367.imagic	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
370.mgrid331	224	NC	NC	NC	NC	NC	NC	112	NC	NC	NC	NC	NC	NC
371.applu331	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC
372.smithwa	224	NC	NC	NC	NC	NC	NC	112	NC	NC	NC	NC	NC	NC
376.kdtree	224	NC	NC	NC	NC	NC	NC	224	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = **NC**

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = **NC**

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## Platform Notes

Sysinfo program /omp2012/Docs/sysinfo  
\$Rev: 395 \$ \$Date:: 2012-07-25 #\$ 8f8c0fe919c65852a1e67685e50647  
running on myhost1 Tue Jun 13 00:19:59 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) Platinum 8180 CPU @ 2.50GHz
 4 "physical id"s (chips)
 224 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores      : 28
siblings       : 56
physical 0:    : 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
25 26 27 28 29 30
physical 1:    : cores 0 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
25 26 27 28 29 30
physical 2:    : cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
25 26 27 28 29 30
physical 3:    : cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
25 26 27 28 29 30
cache size     : 39424 KB
```

From /proc/meminfo

```
MemTotal: 790643032 kB
HugePages_Total: 24576
Hugepagesize: 2048 kB
```

From /etc/\*release\* /etc/\*version\*

```
os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.3 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.3"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.3 (Maipo)"
ANSI_COLOR="0;31"
```

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = **NC**

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = **NC**

OMP2012 license:27  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Jun-2017  
Hardware Availability: Jul-2017  
Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## Platform Notes (Continued)

```
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.3:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.3:ga:server
```

```
uname -a:
Linux myhost1 3.10.0-514.el7.x86_64 #1 SMP Wed Oct 19 11:24:13 EDT 2016
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jun 12 22:00
```

```
SPEC is set to: /omp2012
Filesystem            Size  Used Avail Use% Mounted on
/dev/mapper/rhel100-root 53G   134G  29% /
```

```
Additional information from dmidecode:
BIOS INSYDE Corp. 0.09 03/29/2017
Memory:
8x NO DIMM NO DIMM
24x Samsung M39814K40B1-CTD 32 GB 2666 MHz 2 rank
```

(End of data for sysinfo program)

## General Notes

```
=====  
Power profile set with:  
    all frequency-set -g performance
```

```
System settings notes:  
Intel Turbo Boost Technology (Turbo) : Enabled  
Memory SAS Configuration set to Maximum Performance
```

```
=====  
General Notes and Environment variables  
ENV_KMP_BLOCKTIME=infinite  
ENV_KMP_DETERMINISTIC_REDUCTION=1  
ENV_OMP_DYNAMIC=FALSE  
ENV_KMP_LIBRARY=turnaround  
ENV_KMP_SCHEDULE=static,balanced
```

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = NC

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = NC

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## General Notes (Continued)

```
ENV_KMP_STACKSIZE=256M
ENV_OMP_NESTED=FALSE
ENV_OMP_NUM_THREADS=224
```

```
=====  
General base OMP Library Settings
```

```
ENV_KMP_AFFINITY=granularity=fine,proclist=[0-55,112-167,56-111,168-223],explicit
```

```
=====  
General peak OMP Library Settings
```

```
ENV_KMP_AFFINITY=compact,1
```

```
=====  
Per benchmark peak OMP Library Settings
```

```
=====  
351.bwaves:peak:
```

```
ENV_KMP_AFFINITY=compact,1  
ENV_OMP_SCHEDULE=static,1
```

```
=====  
359.botsspar:peak:
```

```
ENV_KMP_AFFINITY=compact,1  
ENV_OMP_SCHEDULE=guided
```

```
=====  
363.swim:peak:
```

```
ENV_KMP_AFFINITY=compact,1
```

```
=====  
371.applu331:peak:
```

```
ENV_KMP_AFFINITY=granularity=fine,proclist=[0-55,112-167,56-111,168-223],explicit
```

```
=====  
372.smithwa:peak:
```

```
ENV_KMP_AFFINITY=compact,1
```



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = NC

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = NC

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

## Base Portability Flags

350.md: -FR  
357.bt331: -mmodel=medium  
363.swim: -mmodel=medium  
367.imagick: -std=c99

## Base Optimization Flags

C benchmarks:

-O3 -qopenmp -ipo -xCORE-AVX512 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -ansi-alias

C++ benchmarks:

-O3 -qopenmp -ipo -xCORE-AVX512 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -ansi-alias

Fortran benchmarks:

-O3 -qopenmp -ipo -xCORE-AVX512 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -align all

## Peak Compiler Invocation

C benchmarks:

icc

Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = NC

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = NC

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## Peak Compiler Invocation (Continued)

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

## Peak Portability Flags

350.md: -FR  
357.bt331: -mmodel=medium  
363.swim: -mmodel=medium  
367.imagick: -std=c99

## Peak Optimization Flags

C benchmarks:

352.nab: basepeak = yes  
358.botsalgn: basepeak = yes  
359.botspar: basepeak = yes  
367.imagick: basepeak = yes  
372.smithwa: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias  
-opt-streaming-stores always -opt-malloc-options=1  
-ansi-alias

C++ benchmarks:

-O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias -ansi-alias

Fortran benchmarks:

350.md: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias  
-opt-malloc-options=1 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -align array64byte  
Continued on next page



# SPEC OMPG2012 Result

Copyright 2012-2018 Standard Performance Evaluation Corporation

Huawei

SPECompG\_peak2012 = **NC**

Huawei 2488H V5 (Intel Xeon Platinum 8180)

SPECompG\_base2012 = **NC**

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Jun-2017

Hardware Availability: Jul-2017

Software Availability: Apr-2017

**SPEC has determined that this result is not in compliance with the SPEC OMP2012 run and reporting rules. Specifically, the result does not meet the 90 day general availability requirement as the system was not available within 90 days of result publication.**

## Peak Optimization Flags (Continued)

```

351.bwaves: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias
            -fp-model fast=2 -no-prec-div -no-prec-sqrt
            -align array64byte

357.bt331: basepeak = yes

360.ilbdc: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias
           -align array64byte

362.fma3d: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias -no-prec-div
           -no-prec-sqrt

363.swim: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias
          -opt-streaming-cores always -opt-malloc-options=3 -align all

370.mgrid331: -O3 -qopenmp -ipo -xCORE-AVX512 -fno-alias
              -opt-malloc-options=3 -fp-model strict

371.applu331: -O3 -qopenmp -ipo -xCORE-AVX512 -align all

```

The flags file that was used to format this result can be browsed at <http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20170711.html>

You can also download the XML flags source by saving the following link: <http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20170711.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC OMP2012 v1.0.  
Report generated on Mon Jul 30 15:16:51 2018 by SPEC OMP2012 PS/PDF formatter v541.  
Originally published on 11 July 2017.